



FIXING, FASTENING & SUPPORT PRODUCTS

FOR HVAC, PLUMBING,
REFRIGERATION, FIRE PROTECTION
& SEISMIC APPLICATIONS



Loop- & J-Hangers

115FL Standard Duty Loop Hanger, Felt Lined

- Flared edges help prevent sharp surfaces from coming into contact with the pipe
- Recommended for the suspension of stationary non-insulated copper tubing lines to prevent electrolysis
- Felt lining also acts to reduce noise in pipes
- Retained insert nut helps ensure the loop hanger and insert nut stay together
- Manufactured to use the minimum rod size permitted by NFPA[®] for fire sprinkler piping
- Conforms with Federal Specification WW-H-171 (Type 10), Manufacturers Standardization Society (MSS) SP-58 (Type 10)



Material: Steel
Finish: Pregalvanized



Part Number	Description	F ↓	Certifications
1150050FL	1/2" Pipe, 0.84" OD, 3/8" Rod	300 lb	cULus
1150075FL	3/4" Pipe, 1.05" OD, 3/8" Rod	300 lb	cULus, FM
1150100FL	1" Pipe, 1.315" OD, 3/8" Rod	300 lb	cULus, FM
1150125FL	1 1/4" Pipe, 1.66" OD, 3/8" Rod	300 lb	cULus, FM
1150150FL	1 1/2" Pipe, 1.9" OD, 3/8" Rod	300 lb	cULus, FM
1150200FL	2" Pipe, 2.375" OD, 3/8" Rod	300 lb	cULus, FM
1150250FL	2 1/2" Pipe, 2.875" OD, 3/8" Rod	525 lb	cULus, FM
1150300FL	3" Pipe, 3.5" OD, 3/8" Rod	525 lb	cULus, FM
1150400FL	4" Pipe, 4.5" OD, 3/8" Rod	650 lb	cULus, FM

Insert Nut for Loop Hanger

- Insert nut used to attach loop hanger to threaded rod



Material: Steel
Finish: Electrogalvanized

Part Number	Description
100A0050EGP100	100, 101, 115, 116 Series, 1/2" Rod
100N0037EGSP100	101, 115, 116 Series, 3/8" Rod