

CP Thin Wall Conduit Fittings (For EMT Conduit)

- Set Screw Type Fittings
- Compression Type Fittings
- Combination Couplings

Thin Wall
Fittings

COMBINATION COUPLINGS – STEEL

EMT (Set Screw) to Rigid (Set Screw) • Standard material: Steel
UL File No. E-19819 • Standard finish: Zinc plated

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	420	1/2"	25	100	17
	421	3/4"	20	100	25
	422	1"	10	50	37

SET SCREW TYPE FITTINGS – DIE CAST ZINC

Straight Connectors – Insulated

UL File No. E-22132
• Standard material: Zinc
• Standard finish: Natural



	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	1450DC	1/2"	50	500	5
	1451DC	3/4"	30	300	8
	1452DC	1"	15	150	11
	1453DC*	1 1/4"	8	80	20
	1454DC*	1 1/2"	6	60	25
	1455DC*	2"	8	40	37
	1456DC*	2 1/2"	36	24	59
	1457DC*	3"	24	20	78
	1458DC*	3 1/2"	16	12	101
	1459DC*	4"	16	12	120

* Two Tightening Screws

Straight Connectors – Non-Insulated

UL File No. E-22132

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	450DC	1/2"	50	500	5
	451DC	3/4"	30	300	7
	452DC	1"	15	150	11
	453DC*	1 1/4"	8	80	21
	454DC*	1 1/2"	6	60	25
	455DC*	2"	8	40	36
	456DC*	2 1/2"	36	24	58
	457DC*	3"	24	20	77
	458DC*	3 1/2"	16	12	98
	459DC*	4"	16	12	117

* Two Tightening Screws

Couplings

UL File No. E-22132

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	460DC	1/2"	35	350	5
	461DC	3/4"	22	220	7
	462DC	1"	12	120	13
	463DC*	1 1/4"	9	90	18
	464DC*	1 1/2"	6	60	28
	465DC*	2"	8	30	36
	466DC*	2 1/2"	18	12	64
	467DC*	3"	14	10	81
	468DC*	3 1/2"	8	8	98
	469DC*	4"	8	8	116

* Four Tightening Screws

Offset Connectors – Non-Insulated

UL File No. E-22132

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	2400	1/2"	10	100	11
	2401	3/4"	10	100	18
	2402	1"	10	100	25

COMPRESSION TYPE FITTINGS – DIE CAST ZINC

Straight Connectors – Insulated

UL File No. E-22132

• Standard material: Zinc
• Standard finish: Natural



	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	1650DC	1/2"	45	450	8
	1651DC	3/4"	30	300	11
	1652DC	1"	18	180	17
	1653DC	1 1/4"	12	120	31
	1654DC	1 1/2"	8	80	39
	1655DC	2"	3	30	56
	1656DC†	2 1/2"	36	36	93
	1657DC†	3"	20	20	120
	1658DC†	3 1/2"	16	16	149
	1659DC†	4"	16	16	172

Straight Connectors – Non-Insulated

UL File No. E-22132

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	650DC	1/2"	45	450	8
	651DC	3/4"	30	300	11
	652DC	1"	18	180	17
	653DC	1 1/4"	12	120	31
	654DC	1 1/2"	8	80	39
	655DC	2"	3	30	56
	656DC†	2 1/2"	36	36	93
	657DC†	3"	20	20	120
	658DC†	3 1/2"	16	16	149
	659DC†	4"	16	16	172

Couplings

UL File No. E-22132

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	660DC	1/2"	35	350	11
	661DC	3/4"	20	200	16
	662DC	1"	15	150	22
	663DC	1 1/4"	8	80	40
	664DC	1 1/2"	5	50	48
	665DC	2"	2	20	64
	666DC†	2 1/2"	18	18	124
	667DC†	3"	15	15	144
	668DC†	3 1/2"	12	12	190
	669DC†	4"	8	8	228

† Concrete Tight when taped

COMBINATION COUPLINGS – DIE CAST ZINC

EMT (Set Screw) to Rigid (Set Screw) Concrete Tight

UL File No. E-19189

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	2420	1/2"–1 1/2"	50	500	8
	2421	3/4"–3 1/4"	25	250	12