

## Sealing and Insulating – Mastic Tapes

### Scotch® Rubber Mastic Tape 2228

Scotch® Rubber Mastic Tape 2228 is a conformable self-fusing rubber electrical insulating and sealing tape. Scotch® Rubber Mastic 2228 consists of Ethylene Propylene Rubber (EPR) backing coated with a strong, temperature-stable mastic adhesive.


Adhesive Material	Mastic
Backing Material	Ethylene Propylene Rubber (EPR)
Tape Grade	Premium
Tape Type	Sealing and Mastic
Maximum Operating Temperature	Up to 194°F (90°C)
RoHS 2011/65/EU	Yes
Country of Origin	



Order No.	UPC	Color	Length	Width	Thickness	Elongation	Breaking Strength	Rolls per Case
2228-1X10FT	054007-50727	Black	10'	1.00"	65 mil	1000%	10 lbs/in	12
2228-2X10FT	054007-09656	Black	10'	2.00"	65 mil	1000%	10 lbs/in	10
2228-2X3FT	054007-43478	Black	3'	2.00"	65 mil	1000%	10 lbs/in	48

### 3M™ Scotch-Seal™ Mastic Tape Compound 2229

3M™ Scotch-Seal™ Mastic Tape Compound 2229 is designed for quick and easy insulating, padding and sealing of electrical connections. It is a conformable, durable, tacky mastic with an easy release liner for easy applications over irregular surfaces and provides excellent moisture resistance. It features excellent self-healing characteristics after being punctured or cut.

Adhesive Material	Mastic
Backing Material	Rubber
Tape Grade	Premium
Tape Type	Sealing and Mastic
Maximum Operating Temperature	194°F (90°C)
RoHS 2011/65/EU	Yes
Country of Origin	



Order No.	UPC	Color	Length	Width	Thickness	Dielectric Strength	Rolls per Carton	Rolls per Case
2229-1X10FT	054007-50335	Black	10'	1.00"	125 mil	379 v/mil (14.9 kV/mm)	-	12
2229-1.5X30FT	051128-58596	Black	30'	1.50"	125 mil	379 v/mil (14.9 kV/mm)	-	5
2229-3-3/4X10FT	054007-49702	Black	10'	3.75"	125 mil	379 v/mil (14.9 kV/mm)	-	8
2229-P-2-1/2X3-3/4	054007-41303	Black	10'	0.75"	125 mil	379 v/mil (14.9 kV/mm)	-	40
2229-P-3-3/4X3-3/4	054007-50336	Black	10'	3.75"	125 mil	379 v/mil (14.9 kV/mm)	10	40
2229-P-3-3/4X6-1/2	054007-50337	Black	54'	3.75"	125 mil	379 v/mil (14.9 kV/mm)	-	40