



COMMUTATING CHOKE FOR CONVERTER;
 PHASES:3;
 UN1(V):500;
 ITHMAX 1(A) / F1(HZ):250 /50;
 I LN (A):225;
 UK(%):4;
 LN(MH):0,111;
 TA/ISOKL:40 /H;
 IP00;
 TYPE OF TERMINALS:FLAT-TYPE TERMINAL;
 EN 61558-2-20 >CHOKE<

General technical data:

Product designation		Kommut.-Drossel f. Stromrichter
product brand name		SIDAC
Phase number		3
type of voltage		AC
Operating voltage / rated value		
• maximum	V	500
Operating frequency / rated value		
• maximum	Hz	50
Current		
• for AC / rated value	A	225
• for AC / maximum	A	250
• for DC / rated value	A	306.3
Peak current	A	313
Inductivity / rated value	H	0.000111
Relative inductive drop in voltage / on the measurement level current, voltage and frequency	%	4
Effective power loss of the coil	W	174
Effective power loss of the core	W	80

Mechanical design:

Design of the electrical connection / for main current circuit		flat connector
Width	m	0.27
Height	m	0.248
Depth	m	0.187

Ambient conditions:

Thermal class / according to IEC 60085		H
Ambient temperature / rated value	°C	40
Protection class IP		IP00

Certificates/approvals:

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4EU2722-4CA00-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4EU2722-4CA00-0AA0

last change:

Dec 2, 2013