



[On Line Catalog](#)


BURNDY Catalog Number
UPC Number
Description
Status

YA36L2TC38FX
 7818101504055
 HYLUG-450(1100/24)-3/8X1
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Dimensional

Straight
 4.24
 Standard
 Chamfered
 0.39
 Standard
 0.27
 1.38
 1.74
 1.00
 1-3/8

Number of Holes

General

2
 Cu Tubing Hylug, 2 Holes with
 Inspection Window, 450 kcmil
 Flex, 600V-35kV, 3/8" stud,
 Standard, Compression, 0.40 in
 BCD, Brown

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

450 kcmil
 450 kcmil
 450 kcmil
 N/A
 444.4 (1100/#24) DLO
 N/A

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin
 3/8
 Brown
 Y
 20,299
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

12/13/2018

Datasheet - Burndy - YA36L2TC38FX

47 East Industrial Park Drive
Manchester NH 03109

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175