
























## DuraTite® and Ever-Lok® Locking Connections

@ 250V AMPS	VOLTAGE	FACE RECEP./ CONN.	CAT. NOS.						RECEPTACLE — EVER-LOK®	
			PLUG		CONNECTOR		STD. I.D. BUSHING: PLUG/ CONN.*			
			DURATITE®	EVER-LOK®	DURATITE®	EVER-LOK®				
2P3W 20A	125VAC		5P23U1LD	8013U1 8153U1 8593U1	5C23U1LD	8023U1 8093U1 8683U1	.625	8003U1	8083U1	
	250VAC		5P23U2LD	8013U2 8153U2 8593U2	5C23U2LD	8023U2 8093U2 8683U2	.625	8003U2	8083U2	
	277		5P23U3LD	8013U3 8153U3 8593U3	5C23U3LD	8023U3 8093U3 8683U3	.625	8003U3	8083U3	
	480		5P23U4LD	8013U4 8153U4 8593U4	5C23U4LD	8023U4 8093U4 8683U4	.625	8003U4	8083U4	
	600		5P23U5LD	801345 8153U5 8593U5	5C23U5LD	8023U5 8093U5 8683U5	.625	8003U5	8083U5	
	through 600 (all)		5P23U0LD	8013 8153 8593	5C23U0LD	8023 8093 8683	.625	8003N	8083N	
2P3W 30A	125VAC		5P33U1LD	—	5C33U1LD	—	.700	NA	NA	
	250VAC		5P33U2LD	—	5C33U2LD	—	.700	NA	NA	
	277VAC		5P33U3LD	—	5C33U3LD	—	.700	NA	NA	
	480VAC		5P33U4LD	—	5C33U4LD	—	.700	NA	NA	
	600VAC		5P33U5LD	—	5C33U5LD	—	.700	NA	NA	
	through 600 (all)		5P33U0LD	8015 8155 8656	5C33U0LD	8025 8095 8646	.700	8030N	8005N	
3P4W 20A (10A, 600V)	125/250VAC		5P24U1LD	—	5C24U1LD	—	.625	NA	NA	
	3Ø 250VAC		5P24U2LD	—	5C24U2LD	—	.625	NA	NA	
	3Ø 480VAC		5P24U4LD	—	5C24U4LD	—	.625	NA	NA	
	347/600VAC		5P24U5LD	—	5C24U5LD	—	.625	NA	NA	
	through 600 (all)		5P24U0LD	8018 8158 8594	5C24U0LD	8028 8098 8684	.625	8008	8084	
3P4W 30A (20A, 600V)	125/250VAC		5P34U1LD	—	5C34U1LD	—	.750	NA	NA	
	3Ø 250VAC		5P34U2LD	—	5C34U2LD	—	.750	NA	NA	
	3Ø 480VAC		5P34U4LD	—	5C34U4LD	—	.750	NA	NA	
	347/600V		5P34U5LD	—	5C34U5LD	—	.750	NA	NA	
	through 600 (all)		5P34U0LD	8014 8154 8597 8657	5C34U0LD	8024 8094 8687 8647	.750	8031	8004	

**Note:** DuraTite® plugs and connectors will mate but not lock to metal plugs and connectors referenced above. DuraTite® will lock to existing metal receptacles, from standard Ever-Lok® line.

## DuraTite® and Ever-Lok® Locking Connections

### Female Connectors



CLAMP TYPE	MAX. CABLE RATING	BUSHING TYPE	CABLE BUSHING HOLE DIA.	HUB TYPE**	CONDUIT SIZE
8023	1/2"	8093	5/8"	8683N/8683CTN*	1/2"
8023U1	1/2"	8093U1	5/8"	8683U1/8683U1CT*	1/2"
8023U2	1/2"	8093U2	5/8"	8683U2	1/2"
8023U3	1/2"	8093U3	5/8"	8683U3	1/2"
Consult T&B Representative		Consult T&B Representative		Consult T&B Representative	
Consult T&B Representative		Consult T&B Representative		Consult T&B Representative	
8025	5/8"	8095	5/8"	8646	3/4"
8028	1/2"	8098	1 1/16"	8684	1/2"
8024	5/8"	8094	3/4"	8687/8687CT*	1/2"
				8647	3/4"
8324S	3/4"	8394	1"	8386	1/2"
				8387	3/4"

\* Hub with clamp added at size.

\*\* Accommodates rigid conduit or standard connectors for armored and non-metallic cable or flexible conduit.