

Neoprene/EPDM/SBR & EPDM Foam

For information about foam and foam firmness ratings, see page 3568.


Weather-Resistant Neoprene/EPDM/SBR Foam

- Color: Black
- Temperature Range: See below

- Restricts absorption (closed cell)
- Use indoors and outdoors

A combination of the best qualities of these materials creates a resilient, weather- and abrasion-resistant foam rubber. It will also extinguish itself once a flame source is removed—making it good for many electrical applications.

Adhesive-Back Strips—Textured Finish




- Temperature Range: -40° to +158° F
 - Firmness (25% Deflection): 5-9 psi (soft)
 - Density: 5-7 lbs./cu. ft.
- Foam, but not adhesive, meets ASTM D1056 2A2, UL 94HF1, and UL 94HBF. Material has a fine cell textured finish and does not have a skin. Adhesive is rubber based and has a temperature range of -10° to +150° F. Width tolerance is ±0.031" for 1/4" to 1" widths, ±0.063" for 1 1/4" to 4" widths, and ±0.094" for 6" width. Length tolerance is ±3".

Thick.	Thick. Tol.	Length	1/4" Wide	3/8" Wide	1/2" Wide	5/8" Wide	3/4" Wide	1" Wide
1/16"	±0.031"	50 ft.	8694K111 \$3.83	8694K112 \$4.27	8694K113 \$4.73	8694K113 \$5.46	8694K62 \$6.31	8694K63 \$8.03
1/8"	±0.031"	50 ft.	8694K117 4.59	8694K118 5.11	8694K16 5.66	8694K119 6.53	8694K67 7.36	8694K68 9.40
3/16"	±0.031"	50 ft.	8694K124 6.84	8694K125 7.37	8694K17 6.86	8694K126 7.99	8694K72 9.52	8694K73 12.76
1/4"	±0.031"	50 ft.	8694K131 7.15	8694K132 7.73	8694K12 8.81	8694K133 9.18	8694K77 12.29	8694K78 14.94
3/8"	±0.045"	25 ft.	8694K137 5.69	8694K138 5.95	8694K13 6.25	8694K139 7.21	8694K82 9.65	8694K83 10.97
1/2"	±0.045"	25 ft.		8694K144 7.55	8694K14 8.56	8694K145 9.72	8694K87 11.63	8694K88 15.41
3/4"	±0.063"	25 ft.					8694K51 17.14	8694K53 20.16
1"	±0.094"	25 ft.					8694K52 20.51	8694K54 24.68

Thick.	Thick. Tol.	Length	1 1/4" Wide	1 1/2" Wide	2" Wide	3" Wide	4" Wide	6" Wide
1/16"	±0.031"	50 ft.	8694K114 \$9.80	8694K91 \$11.37	8694K64 \$13.89	8694K115 \$21.37	8694K65 \$25.95	8694K116 \$37.62
1/8"	±0.031"	50 ft.	8694K121 11.46	8694K92 13.43	8694K69 16.40	8694K122 24.07	8694K41 29.51	8694K123 44.45
3/16"	±0.031"	50 ft.	8694K127 14.57	8694K93 16.44	8694K74 20.40	8694K128 30.38	8694K42 38.17	8694K129 53.74
1/4"	±0.031"	50 ft.	8694K134 16.81	8694K94 20.21	8694K79 25.38	8694K135 33.60	8694K85 46.23	8694K136 59.73
3/8"	±0.045"	25 ft.	8694K141 13.01	8694K95 15.98	8694K84 21.59	8694K142 28.22	8694K43 42.53	8694K143 53.88
1/2"	±0.045"	25 ft.	8694K146 18.19	8694K96 19.91	8694K89 24.67	8694K147 36.02	8694K57 45.59	8694K148 65.47
3/4"	±0.063"	25 ft.	8694K149 28.18	8694K97 28.71	8694K55 37.54	8694K151 57.45	8694K58 72.92	8694K152 91.92
1"	±0.094"	25 ft.	8694K153 29.89	8694K98 36.79	8694K56 46.88	8694K154 62.36	8694K44 89.81	8694K155 106.25

Sheets and Sheeting—Textured Finish



- Temp. Range: -40° to +200° F
 - Firmness (25% Deflection): 2-5 psi (extra soft), 5-9 psi (soft), or 9-13 psi (firm)
 - Density: Extra soft and soft are 4-8 lbs./cu. ft. and firm is 7-11 lbs./cu. ft.
- Foam meets ASTM D1056, UL 94HF1, MIL-C-3133C, and MIL-STD-670B. Material has a fine cell textured finish and does not have a skin. Sheets have a width tolerance of ±1/4" and a length tolerance of ±2 1/2". Sheeting has a width tolerance of ±1 1/4".

Thick.	Thick. Tol.	42" WD. x 72" LG. SHEETS			42" WIDE SHEETING			
		Extra Soft	Soft	Firm	Max. Lg.	Extra Soft	Soft	Firm
		Each	Each	Each	Per Ft.	Per Ft.	Per Ft.	Per Ft.
1/16"	±0.015"	8647K1 \$19.38	8647K106 \$21.36	8647K109 \$16.06	50 ft. 8647K102 \$3.80	8647K108 \$4.03	8647K12 \$2.92	
1/8"	±0.020"	8647K51 28.63	8647K71 29.62	8647K81 38.96	50 ft. 8647K21 5.49	8647K31 5.57	8647K41 7.77	
3/16"	±0.026"	8647K52 35.21	8647K72 37.09	8647K82 48.35	50 ft. 8647K22 7.44	8647K32 7.62	8647K42 9.61	
1/4"	±0.025"	8647K53 41.79	8647K73 44.38	8647K83 56.92	50 ft. 8647K23 8.32	8647K33 8.80	8647K43 11.25	
3/8"	±0.035"	8647K55 66.90	8647K75 71.03	8647K85 90.66	50 ft. 8647K25 13.26	8647K35 14.69	8647K45 17.99	
1/2"	±0.040"	8647K56 85.29	8647K76 92.08	8647K86 114.04	50 ft. 8647K26 16.95	8647K36 18.90	8647K46 22.45	
3/4"	±0.065"	8647K58 99.61	8647K78 104.80	8647K88 127.63	50 ft. 8647K28 19.93	8647K38 21.89	8647K48 25.76	
1"	±0.082"	8647K59 133.01	8647K79 140.16	8647K89 177.48	50 ft. 8647K29 26.38	8647K39 28.65	8647K49 33.90	
1 1/4"	±0.095"	8647K61 148.75	8647K64 157.23	8647K67 200.68	6 ft. 8647K501 29.74	8647K601 32.81	8647K701 38.47	
1 1/2"	±0.150"	8647K101 167.47	8647K107 178.93	8647K11 265.30	25 ft. 8647K103 42.94	8647K104 43.22	8647K105 52.02	
2"	±0.175"	8647K621 216.11	8647K651 235.86	8647K681 286.82	6 ft. 8647K201 41.72	8647K301 46.26	8647K401 56.24	

Weather-Resistant EPDM Foam

- Color: Black
- Temperature Range: See below

- Restricts absorption (closed cell), unless noted
- Use indoors and outdoors

This expanded EPDM (ethylene-propylene-diene monomer) offers the best weather resistance of the foam materials.


Adhesive-Back Strips—Textured Finish



- Temp. Range: -40° to +220° F
 - Firmness (25% Deflection): 2-5 psi (extra soft)
 - Density: 9-14 lbs./cu. ft.
- Foam, but not adhesive, meets ASTM D1056 2A1. Material has a fine cell textured finish and does not have a skin. Adhesive is acrylic and has a temp. range of -20° to +200° F. Width tolerance is ±1/32". Length tolerance is ±1 ft.

Thick.	Thick. Tolerance	Length	3/8" Wide	1/2" Wide	3/4" Wide	1" Wide
1/8"	±0.032"	50 ft.	93725K52 \$12.81	93725K54 \$15.57	93725K56 \$22.24	93725K58 \$29.11
3/16"	±0.032"	50 ft.	93725K62 14.15	93725K64 18.05	93725K66 26.03	93725K68 33.50
1/4"	±0.032"	50 ft.	93725K72 15.92	93725K74 20.05	93725K76 29.11	93725K78 37.98

Sheeting—Textured Finish



- Temperature Range: -20° to +200° F
- Firmness (25% Deflection): 4-9 psi (soft) or 9-17 psi (firm)
- Absorbent (open cell)
- Density: Soft is 30 lbs./cu. ft. and firm is 35 lbs./cu. ft.

Material has a crisscross textured finish and a skin on the top and bottom. Sheeting is 36" wide. Width tolerance is +1" for 1/8" to 1/4" thick foam and +3" for 3/8" and 1/2" thick foam.

Thick.	Thick. Tolerance	Max. Lg.	Soft	Firm
			Per Ft.	Per Ft.
1/8"	±0.015"	120 ft.	86005K11 \$17.52	86005K51 \$20.47
3/16"	±0.030"	90 ft.	86005K12 24.83	86005K52 28.32
1/4"	±0.030"	60 ft.	86005K13 30.48	86005K53 37.22
3/8"	±0.040"	45 ft.	86005K14 47.11	86005K54 52.29
1/2"	±0.040"	36 ft.	86005K15 59.57	86005K55 66.66

(Material continued on following page)