



"Made with pride in the USA"

**Catalog
CCT-11A**

Fusing chart update



**Effective Date:
June 10, 2011**

Supersedes: CCT-10B

GLOBALTRAN



GlobalTRAN products carry the CE mark, certifying 100% compliance with requirements of EN61558. Additionally all GlobalTRAN products are designed to deliver the full nameplate VA rating.

Features and Benefits

Lead -free solder joints

- Provides RoHS compliant construction

Fully encapsulated coil

- Tough environment-proof construction
- Eases wire routing around the transformer

Molded terminals as an integral part of the coil

- Easily adaptable to slot and Phillips driver tools
- Robust physical support instead of “floating” terminal strips
- Both 4 and 6 terminals, or the combination, available

IP-20 level covers installed

- Meets IEC-529 protection rating

Encapsulated from 25Va through 5KVa

- Establishes product similarity throughout the product range

Full nameplate VA rating

- Eliminates guesswork

Largest standard voltage selection in the industry

- Solves “availability problem” for many OEM design-in opportunities

UL/CSA/cUL/CE Family Listing

- Absolute flexibility of special design capability for 600 volt class product

CE CONTROL TRANSFORMERS

**GLOBALTRAN:
GROUP "G"
CATALOG
NUMBER**

VOLTAGE:
PRI: 380
SEC: 24

	VA	AMPS
B050-2051-GA	50	2.08
B075-2052-GA	75	3.13
B100-2053-GA	100	4.17
B150-2054-GAF	150	6.25
B200-2055-GAF	200	8.33
B250-2056-GAF	250	10.42
B300-2057-GAF	300	12.50
B350-2058-GAF	350	14.58
B500-2059-GAF	500	20.83
B750-2060-GAF	750	31.25

**GLOBALTRAN:
GROUP "I"
CATALOG
NUMBER**

VOLTAGE:
PRI: 208/230/400/460/575
SEC: 24*/115/230

	VA	AMPS
B250-2263-GAF	250	10.4/2.2/1.1
B300-2264-GAF	300	12.5/2.6/1.3
B350-2265-GAF	350	14.6/3.0/1.5
B500-2266-GAF	500	20.8/4.3/2.2
B750-2267-GAF	750	31.3/6.5/3.3
B1K0-2268-GAH	1000	41.7/8.7/4.3
B1K5-2269-GAH	1500	13.04/6.52
B2K0-2270-GAH	2000	17.39/8.70
B3K0-2271-GAH	3000	26.09/13.04
B5K0-2272-GAH	5000	43.48/21.74

* 24 AVAILABLE THROUGH 1Kva

GROUP "H"

VOLTAGE:
PRI: 208-600
SEC: 85-130

	VA	AMPS
B250-2283-GAF	250	1.92
B300-2284-GAF	300	2.31
B350-2285-GAF	350	2.69
B500-2286-GAF	500	3.85
B750-2287-GAF	750	5.77
B1K0-2288-GAH	1000	7.69
B1K5-2289-GAH	1500	11.54
B2K0-2290-GAH	2000	15.38
B3K0-2291-GAH	3000	23.08

GROUP "J"

VOLTAGE:
PRI: 230/400/460/575
SEC: 24/115

	VA	AMPS
B250-2243-GAF	250	10.4/2.2
B300-2244-GAF	300	12.5/2.6
B350-2245-GAF	350	14.6/3.0
B500-2246-GAF	500	20.8/4.3
B750-2247-GAF	750	31.3/6.5
B1K0-2248-GAH	1000	41.7/8.7