


7937A Multi-Conductor - DataTuff® Waterblocked Cate 5e Cable



For more Information
please call

1-800-Belden1



General Description:

24 AWG solid bare copper conductors, twisted pairs, polyolefin insulation, polymer gel waterblocked, inner LLPE jacket, overall Beldfoil shield (100% coverage), 24 AWG stranded TC drain wire, industrial grade sunlight- and oil-resistant LLPE jacket.

Usage (Overall)

Suitable Applications:

Industrial Ethernet Cable, Harsh Environments, 100MHz Category 5e, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, RS-422, CMX - Outdoor, RJ-45 Compatible, Noisy Environments

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material | Dia. (in.) |
|---------|-----|-----------|--------------------|------------|
| 4 | 24 | Solid | BC - Bare Copper | 0.020 |

Total Number of Conductors: 8

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (in.) | Dia. (in.) |
|---------------------|----------------------|------------|
| PO - Polyolefin | 0.009 | 0.038 |

Inner Jacket

Inner Jacket Material:

| Inner Jacket Material | Nom. Dia. (in.) |
|--|-----------------|
| LLPE - Linear Low Density Polyethylene | 0.215 |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | 7x32 | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (in.) |
|--|---------------------------|
| LLPE - Linear Low Density Polyethylene | 0.020 |

Outer Jacket Ripcord: No

Overall Cable

Overall Nominal Diameter: 0.276 in.

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |

7937A Multi-Conductor - DataTuff® Waterblocked Cate 5e Cable

| | |
|---|----------------------------|
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

| | |
|-----------------------------------|-----------------|
| Storage Temperature Range: | -40°C To +85°C |
| Installation Temperature Range: | -25°C To +75°C |
| Operating Temperature Range: | -40°C To +75°C |
| Bulk Cable Weight: | 33 lbs/1000 ft. |
| Max. Recommended Pulling Tension: | 40 lbs. |
| Min. Bend Radius/Minor Axis: | 2.750 in. |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|-------------------------------------|
| EU Directive 2011/65/EU (ROHS II): | Yes |
| Other Standards: | ISO/IEC 11801 ed 2.1 (2008) Class D |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | Category 5e - TIA 568.C.2 |
| Other Specification: | NEMA WC-63.1 Category 5e |

Suitability

| | |
|------------------------|----------------------------|
| Suitability - Outdoor: | Yes |
| Suitability - Burial: | Yes - Telcordia, IEC, ICEA |
| Sunlight Resistance: | Yes |
| Oil Resistance: | Yes |
| Non-halogenated: | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)

15

Maximum Capacitance Unbalance (pF/100 m): 330

Nominal Velocity of Propagation:

VP (%)

70

Maximum Delay:

Delay (ns/100 m)

538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)

45

7937A Multi-Conductor - DataTuff® Waterblocked Cate 5e Cable

Maximum Conductor DC Resistance:

| DCR @ 20°C (Ohm/100 m) |
|------------------------|
| 9.38 |

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 300 V RMS |

Maximum DCR Unbalanced:

| DCR Unbalance @ 20°C (%) |
|--------------------------|
| 3 |

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1 | 2.0 | 65.3 | 62.3 | 63.0 | 60.0 | 20.0 | 23 |
| 4 | 4.1 | 56.3 | 53.3 | 51.0 | 49.0 | 23.0 | 23.0 |
| 8 | 5.8 | 51.8 | 48.8 | 46.0 | 43.0 | 24.5 | 24.5 |
| 10 | 6.5 | 50.3 | 47.3 | 43.0 | 41.0 | 25.0 | 25.0 |
| 16 | 8.2 | 47.3 | 44.3 | 39.0 | 36.0 | 25.0 | 25.0 |
| 20 | 9.3 | 45.8 | 42.8 | 36.5 | 33.5 | 25.0 | 25.0 |
| 25 | 10.4 | 44.3 | 41.3 | 33.9 | 30.9 | 24.3 | 24.3 |
| 31.25 | 11.7 | 42.9 | 39.9 | 31.0 | 28.0 | 23.6 | 23.6 |
| 62.5 | 17.0 | 38.4 | 35.4 | 22.0 | 19.0 | 21.5 | 21.5 |
| 100 | 22.0 | 35.3 | 32.3 | 14.0 | 11.0 | 20.1 | 20.1 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1 | 100 ± 15 | 100 ± 15 | 63.8 | 60.8 |
| 4 | 100 ± 15 | 100 ± 15 | 51.7 | 48.7 |
| 8 | 100 ± 15 | 100 ± 15 | 45.7 | 42.7 |
| 10 | 100 ± 15 | 100 ± 15 | 43.8 | 40.8 |
| 16 | 100 ± 15 | 100 ± 15 | 39.7 | 36.7 |
| 20 | 100 ± 15 | 100 ± 15 | 37.7 | 34.7 |
| 25 | 100 ± 15 | 100 ± 15 | 35.8 | 32.8 |
| 31.25 | 100 ± 15 | 100 ± 15 | 33.9 | 30.9 |
| 62.5 | 100 ± 15 | 100 ± 15 | 27.8 | 24.8 |
| 100 | 100 ± 15 | 100 ± 15 | 23.8 | 20.8 |

Notes (Overall)

Notes: Operating temperatures are subject to length de-rating. Cable passes -40°C Cold Bend per UL 1581. Sequential marking at two foot intervals. Polymer gel waterblocking material.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|-------|-------|--------------------------------|
| 7937A 0101000 | 1,000 FT | 38.000 LB | BLACK | | 4 PR #24 P0 GEL LLDPO FS LLDPO |

Revision Number: 1 Revision Date: 08-02-2013

© 2013 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge,

7937A Multi-Conductor - DataTuff® Waterblocked Cate 5e Cable

information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.