

## CDB-38-70015 Product Details



**CDB-38-70015**

### Time Delay Relays

Not EU RoHS or ELV Compliant

#### Product Highlights:

- CD Series
- Input Voltage = 120 VAC
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 30 VDC or 277 VAC
- Mounting Options = Socket

TE Internal Number: 5-1393136-0

 Active

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">CD CMOS IC Time Delay Relay</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Additional Product Images:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Schematic</a></li> <li>• <a href="#">Wiring Diagram</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• Series = CD</li> <li>• Termination Type = 11-Pin Octal Style Plug</li> </ul> <p><b>Mechanical Attachment:</b></p> <ul style="list-style-type: none"> <li>• Mounting Options = Socket</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• Input Voltage (VAC) = 120</li> <li>• Contact Rating = 10A @ 30 VDC or 277 VAC</li> </ul> <p><b>Dimensions:</b></p> <ul style="list-style-type: none"> <li>• Approx. Dimensions (L x W x H) (mm [in]) = 61.10 x 45.20 x 74.60 [2.407 x 1.780 x 2.939]</li> </ul> <p><b>Body Features:</b></p> <ul style="list-style-type: none"> <li>• Enclosure Type = Yellow Plastic Case</li> </ul> <p><b>Contact Features:</b></p> <ul style="list-style-type: none"> <li>• Delay Time = 1.8 seconds to 180 seconds</li> <li>• Type of Control = Knob</li> <li>• Repeatability, Max. = <math>\pm 1\%</math></li> <li>• Contact Base Material = Silver Cadmium Oxide</li> </ul>	<p><b>Configuration Features:</b></p> <ul style="list-style-type: none"> <li>• Contact - Arrangement = 2 Form C, DPDT, 2 C/O</li> <li>• Multiple Timing Ranges = Without</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• Approved Standards = CSA Certified, UL Recognized</li> <li>• RoHS/ELV Compliance = Not ELV/RoHS compliant</li> <li>• Lead Free Solder Processes = Not relevant for lead free process</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• Temperature Range (°C) = -40 - +55</li> </ul> <p><b>Operation/Application:</b></p> <ul style="list-style-type: none"> <li>• Mode of Operation = Delay on Release</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Potter &amp; Brumfield</li> </ul>