

**Plastic  
Connectors**




PC 6100		105°	Nylon K.O. Bushings		ABS
Cat. No.	UPC	Description	Unit	Std.	
1210D	12100	1/2" Nylon K.O. Bushing	100	1000	
1211D	12110	3/4" Nylon K.O. Bushing	100	1000	
1212D	12120	1" Nylon K.O. Bushing	100	1000	
1213D	12130	1-1/4" Nylon K.O. Bushing	50	500	
1214D	12140	1-1/2" Nylon K.O. Bushing	25	250	
1215D	12150	2" Nylon K.O. Bushing	25	250	
1216D	12160	2-1/2" Nylon K.O. Bushing	25	250	

**Flame Retardant**  
Made of Ultramid  
Type 6 Nylon



PC «so		Single	NMC Connectors		Nylon
Snap-In IS'o Tool					
Cat. No.	UPC	Description	Size	Unit	Std.
1200D	12000	One 14-2, or 12-2	1/2"	100	1000



PC 6070		NMC Cable Connectors		Plastic
Cat. No.	UPC	Description	Unit	Std.
NMC 50	10160	Cable and Cord 1/2" Connectors	100	1000

- **NON-METALLIC**
- COSTS LESS
- RESISTS CORROSION
- ONE OR TWO CRIES
- ALLFUSTIC RESIGN
- EXCELLENT INSOLATION
- STRAIN RELIEF

**for NMC (non-metallic cable) & Flexible Cord**  
**Size: To Fit 1/2" Knockout**

**Dottle's** new nonmerallic sheathed cable connector for Romex cable is a "SNAP" to install. Molded in a one piece plastic construction, this push in design has a captive locking wedge. The cable will be securely retained and no locknut is required. The multipurpose design offers total insulation and is lightweight with excellent strain relief. It is designed to accommodate single 14-2 min. to 10-3 max., two 14-2 min. to 12-2 max cables, and one or more .300 inch to .600 diameter cords. Rigid PVC and sized to fit 1/2" knockout.

**Snap in Box      Run Cable      Insert Locking Wedge      Tighten      Done!**

