


IT 5462 Die Cast

Weathertight Hubs For Rigid Conduit

Fittings

Cat. No.	I ¹ PC	Size		Unit	Std.
\VTH50	60255	1/2"	Insulated	10	100
WTH75	60256	3/4"	Insulated	10	100
WTH100	60257	1"	Insulated	10	100
WTH125	60258	1-1/4"	Insulated	5	50
WTH150	60259	1-1/2"	Insulated	5	50
WTH200	60260	2"	Insulated	2	20
WTH250	60261	2-1/2"	Insulated	1	5
VCTH30Q	60262	3"	Insulated	1	5
WTH350	60263	3-1/2"	Insulated	1	5
WTH400	60264	4"	Insulated	1	5




K: 5464 Die Cast

Weathertight Hubs w/Lugs For Rigid Conduit

NEW

Cat. No.	UPC	Size		Unit	Std.
WTHGL50	60270	1/2"	Insulated w/Lugs	10	100
WTHGL75	60271	3/4"	Insulated w/Lugs	10	100
WTHGL100	60272	1"	Insulated w/Lugs	10	100
WTHGL125	60273	1-1/4"	Insulated w/Lugs	5	50
WTHGL150	60274	1-1/2"	Insulated w/Lugs	5	50
WTHGL200	60275	2"	Insulated w/Lugs	2	20
WTHCL250	60276	2-1/2"	Insulated w/Lugs	1	10
WTHGL300	60277	3"	Insulated w/Lugs	1	10
WTHGL350	60278	3-1/2"	Insulated w/Lugs	1	10
WTHGL400	60279	4"	Insulated w/Lugs	1	10

with
Ground Lugs

PC 5530 Steel

No Thread Connectors for Rigid Conduit

Cat. No.	UPC	Size		Unit	Std.
NT50	66750	1/2"	Non Insulated	25	125
NT75	66752	3/4"	Non Insulated	25	125
NT100	66754	1"	Non Insulated	10	50
NT125	66756	1-1/4"	Non Insulated	10	50
NT150	66758	1-1/2"	Non Insulated	5	25
NT200	66780	2"	Non Insulated	5	25
NT50-I	66760	1/2"	Insulated	25	125
NT75-I	66762	3/4"	Insulated	25	125
NT100-I	66764	1"	Insulated	10	50
NT125-I	66766	1-1/4"	Insulated	10	50
NT150-I	66768	1-1/2"	Insulated	5	25
NT200-I	66782	2"	Insulated	5	25



it 5530 Steel

No Thread Couplings For Rigid Conduit

Cat. No.	UPC	Size		Unit	Std.
NTC50	66770	1/2"		25	125
NTC75	66772	3/4"		25	125
NTC100	66774	1"		15	75
NTC125	66776	1-1/4"		5	25
NTC150	66778	1-1/2"		5	25
NTC200	66784	2"		5	25

