

## FINISH/BRAD NAILERS



16 Gauge 1" - 2-1/2" (25.4 mm - 63.5 mm) Finish Nailer



15 Gauge 1" to 2-1/2" (25.4 mm - 63.5 mm) Finish Nailer



18 Gauge 2" (63.5 mm) Brad Nailer Kit

SPECIFICATIONS	D51257K	D51276K	DWFP12231
Nail Diameter	16 Gauge	15 Gauge "Da" Style Nails	18 Gauge
Nail Length Capacity	1" - 2-1/2"	1" - 2-1/2"	5/8" - 2"
Magazine Angle	Straight	34°	Straight
Magazine Capacity	100 Nails	100 Nails	100 Nails
Magazine Loading	Rear Load, Load & Lock / Lock & Load	Rear Load, Load & Lock / Lock & Load	Side Load
Operating Pressure	70 - 120 psi	70 - 120 psi	70 - 120 psi
Depth Setting	Tool-Free Thumb Wheel	Tool-Free Thumb Wheel	Tool-Free Thumb Wheel
No Mar Pad	Low Profile Rubber	Low Profile Rubber	Low Profile Rubber
Integrated Belt Hook	Tool-Free Adjustable	Tool-Free Adjustable	Tool-Free Adjustable
Jam Clearing	Tool-Free Front Opening	Tool-Free Front Opening	Tool-Free Front Opening
Includes	Sample finish nails and 1/4" air fitting	Sample finish nails and 1/4" air fitting	Sample brad nails and 1/4" air fitting

## FINISH NAILS



CAT #	DESCRIPTION	LENGTH	BOX QTY.
<b>15 GAUGE "DA" Angled Finish Nails</b>			
DCA15150	"DA" Angle Finish Nails	1-1/2" (38.1 mm)	4,000
DCA15200	"DA" Angle Finish Nails	2" (50.8 mm)	4,000
DCA15250	"DA" Angle Finish Nails	2-1/2" (63.5 mm)	4,000
DCA15250G	Angle Finish Nail Galv	2-1/2" (63.5 mm)	4,000
<b>16 GAUGE 20° Angled Finish Nails</b>			
DCA16125	"FN" Angle Finish Nails	1-1/2" (38.1 mm)	2,500
DCA16150	"FN" Angle Finish Nails	2" (50.8 mm)	2,500
DCA16200	"FN" Angle Finish Nails	2-1/2" (63.5 mm)	2,500
DCA16250	"FN" Angle Finish Nails	2-1/2" (63.5 mm)	2,500

CAT #	DESCRIPTION	LENGTH	BOX QTY.
<b>18 GAUGE Straight Brad Nails</b>			
DBN18063	Brad Nail	5/8" (15.8 mm)	5,000
DBN18125	Brad Nail	1-1/4" (31.7 mm)	5,000
DBN18150	Brad Nail	1-1/2" (38.1 mm)	5,000
DBN18200	Brad Nail	2" (50.8 mm)	5,000
<b>16 GAUGE Straight Finish Nails</b>			
DCS16125	Straight Finish Nails	1-1/4" (31.7 mm)	2,500
DCS16150	Straight Finish Nails	1-1/2" (38.1 mm)	2,500
DCS16200	Straight Finish Nails	2" (50.8 mm)	2,500
DCS16250	Straight Finish Nails	2-1/2" (63.5 mm)	2,500



## PAPER TAPE FRAMING NAILS



CAT #	Head Type	Length	Diameter	Shank	Finish	Box Qty.
DPT-10D120FH	Off-Set Round Head	3"	.120"	Smooth	Bright	2500
DPT-10D120GFH	Off-Set Round Head	3"	.120"	Smooth	Galvanized	2000
DPT-10D131FH	Off-Set Round Head	3"	.131"	Smooth	Bright	2500
DPT-10DR120GFH	Off-Set Round Head	3"	.120"	Ring	Galvanized	2000
DPT-12D120FH	Off-Set Round Head	3-1/4"	.120"	Smooth	Bright	2500
DPT-12D131FH	Off-Set Round Head	3-1/4"	.131"	Smooth	Bright	2500
DPT-12D131GFH	Off-Set Round Head	3-1/4"	.131"	Smooth	Galvanized	2000
DPT-16D131FH	Off-Set Round Head	3-1/2"	.131"	Smooth	Bright	2000
DPT-6D113FH	Off-Set Round Head	2"	.113"	Smooth	Bright	5000
DPT-8D113FH	Off-Set Round Head	2-3/8"	.113"	Smooth	Bright	5000
DPT-8D113GFH	Off-Set Round Head	2-3/8"	.113"	Smooth	Galvanized	2000
DPT-8DR113FH	Off-Set Round Head	2-3/8"	.113"	Ring	Bright	5000
DPT-8DR113GFH	Off-Set Round Head	2-3/8"	.113"	Ring	Galvanized	2000
DPTS6DR113G	Clipped	2"	.113"	Ring	Galvanized	1000
DPTS8DR113	Clipped	2-3/8"	.113"	Ring	Bright	1000
DPTS8DR113G	Clipped	2-3/8"	.113"	Ring	Galvanized	1000
DPTS10D120	Clipped	3"	.120"	Smooth	Bright	1000
DPTS10DR120G	Clipped	3"	.120"	Ring	Galvanized	1000
DPTS10D131	Clipped	3"	.131"	Smooth	Bright	1000
DPTS12D131G	Clipped	3-1/4"	.131"	Smooth	Galvanized	1000

Compatible with most cordless and pneumatic paper tape nailers, including those made by DEWALT®, BOSTITCH®, PORTER-CABLE®, Paslode®, and Senco®

## ROOFING NAILER



3/4" - 1-3/4" (19 mm - 44.4 mm) Coil Roofing Nailer

SPECIFICATIONS	DWFP12658
Nail Style	Coil Roofing
Nail Diameter Range	.120"
Nail Length Capacity	3/4" - 1-3/4"
Canister Capacity	120 Nails
Operating Pressure	70 - 120 psi
Canister Loading	2-Door Side Load
Nose Piece Carbide Inserts	Yes
Selectable Trigger	Yes
Jam Clearing	Tool-Free Integrated In Nose Door
Includes	Nailer oil

## FLOORING TOOL



2-in-1 Flooring Tool

SPECIFICATIONS	DWFP12569
Nail Style	Staples and "L" Cleat Nails
Nail Diameter Range	15.5 GA Staples and 16 ga "L" Cleat Nails
Nail Length Capacity	1-1/2" - 2"
Canister Capacity	135 Cleats or 115 staples
Operating Pressure	70 - 100 psi
Canister Loading	Top Loading
Tool Base	Non-marring, interchangeable base plates
Selectable Trigger	Mallet Actuation
Jam Clearing	-
Includes	Mallet and 1/4" air fitting