MICRO SWITCH
A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR COMPANY
FREEPORT, ILLINOIS
FED. MFR. CODE 91929

SWITCH - TOGGLE (MAGNETIC HOLD-IN)

CATALOG LISTING
26ET57-T





CIRCUIT DIAGRAM
(MECHANICALLY MAINTAINED POSITION)

NOTES
1 - EXPOSED PARTS ARE OF CORROSION RESISTANT MATERIAL OR ARE SUITABLY PROTECTED TO PREVENT CORROSION. ENCLOSURE FINISHED WITH BLUE EPOXY-BASED ENAMEL COLOR NO. 25184 PER FEDERAL STANDARD 595
2 SWITCH SEALED PER MIL-S-5594
3 HOLD IN VOLTAGE: THE MINIMUM SPECIFIED VOLTAGE AT WHICH THE LEVER WILL REMAIN ACTUATED. HOLD IN MAY OCCUR AT A LOWER VALUE
DROP OUT VOLTAGE: THE VOLTAGE RANGE IN WHICH THE LEVER WILL BE RELEASED
4 - CIRCUITS CAN BE TRANSFERRED MANUALLY. ENERGIZING THE COIL WILL NOT CAUSE TRANSFER OF CIRCUITS
5 CIRCUIT IDENTIFICATION IS SHOWN ON SWITCH
6 - SWITCHES DO NOT NECESSARILY OPERATE SIMULTANEOUSLY
7 HARDWARE MAYBE FURNISHED UNASSEMBLED PER MIL-S-5594

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS 3

SOLENOID RATING AT 20° C
STEADY STATE LIMITS - - - - 20 - 29 VDC
HOLD IN - - - - - - - - - - - - - - - 15 VDC
DROP OUT - - - - - - - - - - - - 0 - 15 VDC
OVERRIDE FORCE AT 30 VDC - - - 5 LB MAX
COIL RESISTANCE - - - - 460 OHM MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T (2)

VOLTAGE	RATING IN AMPERES							
	SEA LEVEL				65,000 FT			
	RES	IND	MOTOR		RES	IND	MOTOR	
28 VOLTS DC	4	3	4		4	2.5	4	

SCALE FULL
DO NOT SCALE PRINT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCES ARE:

ONE PLACE	(.0)	±.030
TWO PLACE	(.00)	±.015
THREE PLACE	(.000)	±.005
ANGLES		±

WEIGHT 4.0 OZ MAX

REVISIONS						
LTR	DRAWN	CHECK	ISSUE	DRAWING NUMBER	RELEASE NO.	REPLACES
A	C O 44802 D J S 5 OCT 78		X2	M 26ET57-T	PR-5259	
B	CO 50162 WJM 6 OCT 81		X4			
C	CO-53401 J A S 16 MAR 84					
D	18 NOV 75					
E	10 NOV 75					

FC-80378-003