

MICRO SWITCH

FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

SWITCH-ENCLOSED

CATALOG LISTING 26CX SERIES

CHART 1

CONVERSION CHART

5,55	.219
7,25	.285
7,29	.287
8,5	.33
9,4	.37
12,7	.50
17,8	.70
18,3	.72
20,3	.80
22,3±1,5	.880±.059
25,4	1.00
32,0	1.26
40,0	1.57
50,8	2.00
60,35	2.38
80,0	3.15
97,0	3.82
101,6	4.00
133,0	5.24
145,0	5.71
1,25 Nm	.922 PF
0,113 Nm	.083 PF
1,25 Kg	2.75 LB

26CX SERIES
CHART 1

M

DRAWING
NUMBER

13

ISSUE

RELEASE NO. PR-12361

CHECK

REVISIONS

A PR22267

J A K
5 AUG 96

B 201884

JAH
12 DEC 00

CHECK


25 AUG 83

CHECK

22 AUG 83

CHECK

WJM




NOTES

- 1 - EXPLOSION PROOF-UNDERWRITERS LAB INC LISTING FOR HAZARDOUS LOCATIONS CLASS I, GROUPS B, C, AND D; CLASS II, GROUPS E, F AND G
- 2 - ALUMINUM ENCLOSURE FINISHED WITH BLUE AND BLACK EPOXY PAINT
- 3 - 6-32 UNC X 5,55/REF BINDING HEAD TERMINAL SCREW AND CUP WASHER (3 PER BASIC)
- 4 - CAMS MAY BE REPOSITIONED IN 7°20' INCREMENTS
- 5 - FOR USE IN TEMPERATURES UP TO 85°C
- 6 SEE (M) 7CX CHART 1 AND 2 FOR LEVER ACTUATORS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



SCALE 3/4 TO 1

DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

DIM.	TOL.	DIM.	TOL.
mm	mm/in	in	mm/in
NO PLACES	X	1/64	X
ONE PLACE	X.X	0.01/0.05	X.X
TWO PLACES	X.XX	0.001/0.005	X.XX
THREE PLACES	X.XXX	0.0001/0.0005	X.XXX

DESIGN UNITS

SI METRIC ☒ US CUSTOMARY ☐

RAW MATERIAL-COMMERCIAL STANDARD

MICRO SWITCH STANDARDS APPLY

DIMENSIONS ARE TO BE MET BEFORE

PROTECTIVE COATINGS ARE APPLIED

WEIGHT 1,25 Kg APPROX

CHARACTERISTICS 26CX

OPERATING FORCE ---	1,25 Nm MAX
RELEASE FORCE ---	0,113 Nm MAX
PRETRAVEL ---	30° MAX
DIFFERENTIAL TRAVEL ---	20° MAX
OVERTRAVEL ---	75° MIN

CONTACT ARRANGEMENT SPDT (EACH BASIC)

CAT. LIST.	DESCRIPTION	ELECTRICAL DATA
		UL LISTED - FILE E14274 CODE L22 1A-125 VAC
26CX4C	4 BASICS: EACH OPERATES CLOCKWISE AND COUNTER CLOCKWISE	
26CX4	4 BASICS: EACH OPERATES CLOCKWISE AND COUNTER CLOCKWISE	
B	3 BASICS: EACH OPERATES CLOCKWISE AND COUNTER CLOCKWISE	