

- NOTES
- 1 - CORROSION RESISTANT STEEL ENCLOSURE
 - 2 - SWITCH SEALED PER MIL-PRF-8805 SYMBOL 4
 - 3 - CIRCUIT DIAGRAM, CATALOG LISTING, AND DATE CODE ARE SHOWN ON NAMEPLATE
 - 4 - COINCIDENCE OF OPERATING AND RELEASING POINTS: .010 INCH OF PLUNGER TRAVEL
 - $\triangle 5$ TO ADJUST ROLLER DIRECTION REMOVE ROLLER GUIDE LOCK RING SCREW ROLLER GUIDE TO DESIRED DIRECTION, SECURE BY REPLACING ROLLER GUIDE LOCK RING
 - $\triangle 6$ BIFURCATED GOLD CONTACT BASIC SWITCHES
 - $\triangle 7$ REPLACEMENT MOUNTING HARDWARE - PACKET 19PA9
 - $\triangle 8$ REPLACEMENT ROLLER GUIDE AND LOC RING - PACKET 15PA105
 - $\triangle 9$ REPLACEMENT LOCK RING - PACKET 15PA107
 - $\triangle 10$ HARDWARE MAY BE PACKAGED UNASSEMBLED PER MIL-PRF-8805

CATALOG LISTING
622EN233-6
PAGE 1 OF 1

REPLACES
RELEASE NO. 203748

ISSUE
M
1

REVISIONS

CHECK

CHECK

21AUG01

SAV

CHECK

21AUG01


RASTER
DRAWN

KED

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

THIRD ANGLE PROJECTION



SCALE FULL

DO NOT SCALE PRINT

CHARACTERISTICS	
OPERATING FORCE	6-12 LB
FULL OVERTRAVEL FORCE	30 LB MAX
RELEASE FORCE	4 LB MIN
PRETRAVEL	.040 MAX
DIFFERENTIAL TRAVEL	.020 MAX
OVERTRAVEL	.125 MIN

ELECTRICAL DATA		
CONTACT ARRANGEMENT		
2X S P D T		
LOAD	28 VDC $\triangle 6$	
	SEAL LEVEL	50,000 FT
RES	1.0	1.0
IND	0.5	0.5
MOTOR	---	---

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
ONE PLACE (.0)	\pm .030
TWO PLACE (.00)	\pm .015
THREE PLACE (.000)	\pm .005
ANGLES	\pm
WEIGHT	