MICRO SWITCH
FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH-BASIC

CATALOG LISTING
6HM1-6



NOTE

1. MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .087 MAX DIA ON .375 ± .002 CENTERS
2. – FOR USE IN TEMPERATURE RANGE −85°F TO +500°F (DOWN TO −300° IF WIRE LEADS ARE NOT FLEXED)
3. – HERMETICALLY SEALED (METAL-TO-METAL, GLASS-TO-METAL)
4. – ALL EXPOSED PARTS ARE OF CORROSION RESISTANT MATERIALS
5. – WEIGHT OF SWITCH ONLY IS 0.014 LB MAX. WEIGHT OF CONDUCTOR GROUP ONLY IS 0.013 LB MAX PER FOOT
6. – DO NOT APPLY MORE THAN 1 1/2 INCH-LBS OF TORQUE WHEN TIGHTENING MOUNTING SCREWS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

OPERATING FORCE — — — — — — — 7 OZ MAX
RELEASE FORCE — — — — — — — 1 OZ MIN
DIFFERENTIAL TRAVEL — — — — .006 MAX
OVERTRAVEL — — — — — — — — .003 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

LINE VOLTAGE	INDUCTIVE LOAD	RESISTIVE LOAD
28 VDC	2 AMP	4 AMP
115 VAC (400 CYCLE)	2 1/2 AMP	2 1/2 AMP

SCALE 2:1
DO NOT SCALE PRINT

UNLESS OTHERWISE NOTED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:

ONE PLACE	(.0)	±.030
TWO PLACE	(.00)	±.015
THREE PLACE	(.000)	±.005
ANGLES		±

WEIGHT 5

REPLACES
RELEASE NO. PR-347
DRAWING NUMBER 6HM1-6
M
ISSUE 8
CHECK

REVISIONS

A	NEW DWG	ORD 21 FEB 68
B	PR-347	GFS 4 SEPT 68
C	CO-32230	BEN 23 JUL 73
D	CO 51888	WJM 20 SEP 82
E	CO71228	DAW 1 NOV 91
F	CO80788	SAD 22 APR 95

CHECK
LSD 21 FEB 68
CHECK
DRAWN ORD 20 FEB 68
FO-50378