**MICRO SWITCH**
a Honeywell Division
FED.MFG.CODE 91929

# SWITCH – BASIC

CATALOG LISTING
**6HM42-1**




NOTES
1. MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF Ø .087 MAX ON .375±.002 CENTERS
2. – FOR USE IN TEMPERATURE RANGE –85°F TO +500°F (DOWN TO –300°F IF WIRE LEADS ARE NOT FLEXED
3. – HERMETICALLY SEALED (METAL TO METAL, METAL TO GLASS)
4. – ALL EXPOSED PARTS ARE OF CORROSION RESISTANT MATERIALS
5. WEIGHT OF SWITCH ONLY IS 0.22 OZ MAX. WEIGHT OF CONDUCTOR GROUP ONLY IS 0.14 OZ MAX PER FOOT
6. – DO NOT APPLY MORE THAN 1 1/2 INCH LBS OF TORQUE WHEN TIGHTENING MOUNTING SCREWS

ANSI Y14.5M–1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

| CHARACTERISTICS | |
|---|---|
| OPERATING FORCE | 7 OZ MAX |
| RELEASE FORCE | 1 OZ MIN |
| DIFFERENTIAL TRAVEL | .004 MAX |
| OVERTRAVEL | .003 MIN |

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P N O

| LINE VOLTAGE | INDUCTIVE LOAD | RESISTIVE LOAD |
|---|---|---|
| 28 VDC | 2 AMP | 4 AMP |
| 115 VAC (400 CYCLE) | 2 1/2 AMP | 2 1/2 AMP |

SCALE 2:1 — DO NOT SCALE PRINT

**UNLESS OTHERWISE SPECIFIED TOLERANCES ARE**

| | | |
|---|---|---|
| ONE PLACE | (.0) | ±.030 |
| TWO PLACE | (.00) | ±.015 |
| THREE PLACE | (.000) | ±.005 |
| ANGLES | | ± |

WEIGHT 5

CATALOG LISTING 6HM42-1 | PAGE 1 OF 1 | ISSUE 7

REVISIONS

| | | |
|---|---|---|
| A | OBS C078867 | CSL 17 AUG 94 |
| B | REINST PR22428 | JAK 27 SEP 96 |

RELEASE NO. PR-2952 | REPLACES

DRAWN JAK 30 SEP 96 | CHECK | CHECK | CHECK | CHECK

DDM/CAD