



# Crimp Tools



## Pneumatic Crimp Tool

- Model AT-200 hand-held pneumatic crimp tool weighs less than 2 lbs.
- Performs high volume output with less operator fatigue.
- Offers consistent, high-quality crimped terminals.
- Operates using standard shop air (85-95 PSI).
- Die changeover complete in less than two minutes.
- Perfect for assembly line operation.
- Crimps wires ranging from 26 AWG to 8 AWG.

Model	Description	Cat. No.
AT-200	Pneumatic Crimp Tool Frame	30-847
AT-7000	Die for Model NC-1610 and Model 49 closed-end splices	30-846
AT-7050	Die for Model NC-2212 closed-end splice	30-845
AT-BA	Bench Mount for Model AT-200	30-844




## IDEAL Crimpmaster™ Crimp Tool

- Designed to provide a high-quality, ratchet type crimp.
- Full-cycle ratchet provides repeatable and reliable terminations.
- Interchangeable dies provide versatility in a single tool.
- Crimp release provides operator safety.




Description	Cat. No.
IDEAL Crimpmaster™ Crimp Tool Frame	30-506
Tool with die for fully insulated slide on connectors 22-10 AWG	30-477
Tool with die for non-insulated open barrel crimps 22-12 AWG	30-480
Tool with die for miniature insulated rings and splices 16-26 AWG	30-487
Tool with die for insulated ring tongue terminals 22-10 AWG	30-500
Tool with die for non-insulated terminals 22-8 AWG	30-501
Tool with die for Model 49 closed-end splices	30-492
Tool with die for NC-8 closed-end splices	30-493


**30-594 - Die only**  
**30-487 - Tool with die**  
 22-10 AWG (.324 mm<sup>2</sup> - 5.261 mm<sup>2</sup>)  
 Fully insulated quick disconnect terminals with thinner wire barrels




**30-586 - Die only**  
**30-480 - Tool with die**  
 22-12 AWG (.324 mm<sup>2</sup> - 3.31 mm<sup>2</sup>)  
 Non-insulated open barrel connectors, commercial type




**30-572 - Die only**  
**30-487 - Tool with die**  
 16-26 AWG (1.31 mm<sup>2</sup> - .128 mm<sup>2</sup>)  
 Miniature insulated rings, spade and butt splices



**30-579 - Die only**  
**30-500 - Tool with die**  
 22-10 AWG (.324 mm<sup>2</sup> - 5.261 mm<sup>2</sup>)  
 Insulated terminals/color coded nests



**30-580 - Die only**  
**30-501 - Tool with die**  
 22-8 AWG (.3 mm<sup>2</sup> - 8 mm<sup>2</sup>)  
 Non-insulated terminals



**30-491 - Die only**  
**30-492 - Tool with die**  
 18-12 AWG  
 Model 49 closed-end splices

