

Safety Signs



- Bright, colorful signs identify potentially hazardous work areas
- Fiberglass reinforced plastic, self-sticking polyester or flexible magnetic construction
- Resistant to both chemicals and abrasion – protected graphics for indoor and outdoor use



Legend	Material	Size (In.)	Cat. No.
Lock Out Before Servicing	Self-sticking polyester	2-1/4 x 4-1/2	44-884



Legend	Material	Size (In.)	Cat. No.
Notice In Accordance with OSHA	Reinforced plastic	20 x 14	44-887



Legend	Material	Size (In.)	Cat. No.
Danger High Voltage	Reinforced plastic	10 x 14	44-862
Danger High Voltage	Self-sticking polyester	7 x 10	44-863
Danger High Voltage Keep Out	Reinforced plastic	10 x 14	44-880
Danger High Voltage Keep Out	Self-sticking polyester	7 x 10	44-881



ALTO VOLTAJE
MANTENGASE ALEJADO



HIGH VOLTAGE
KEEP OUT

Legend	Material	Size (In.)	Cat. No.
Danger High Voltage – Spanish	Self-sticking polyester	7 x 10	44-865
Danger High Voltage – Bilingual	Reinforced plastic	20 x 14	44-882



Legend	Material	Size (In.)	Cat. No.
Danger Breakers Locked Out –	Magnetic	5 x 7	44-890
Danger Equipment Being Serviced Do Not Operate	Magnetic	5 x 7	44-891

AREA IN FRONT OF THIS ELECTRICAL PANEL MUST BE KEPT CLEAR FOR 36 INCHES OSHA-NEC REGULATIONS

EL AREA EN FRENTE DE ESTE PANEL ELECTRICO DEBE MANTENERSE DESPEJADA POR 36 PULGADAS DE ACUERDO CON LAS REGULACIONES DE OSHA-NEC

Legend	Material	Size (In.)	Cat. No.
OSHA Regulation	Self-sticking polyester	3-1/2 x 10	44-877
OSHA Regulation – Bilingual	Self-sticking polyester	7 x 10	44-878