



L.H. Dottie Company
 6131 Garfield Avenue
 Commerce, California 90040
 Call: 323-725-1000 • Fax: 323-721-0000

“Building a Better Brand”

Insulated Weathertight Mechanical Hubs

Weathertight hubs are used to terminate rigid conduit or IMC into an enclosure.



1

<u>Item #</u>	<u>Item Name</u>	<u>Material</u>	<u>Size</u>	<u>Package Length</u>	<u>Package Width</u>
<u>WTH50</u>	(WTH50) Insulated Weathertight Mechanical Hub	Zinc Alloy	1/2 in.	5.2 in.	3.80 in.
<u>WTH75</u>	(WTH75) Insulated Weathertight Mechanical Hub	Zinc Alloy	3/4 in.	5.2 in.	3.7 in.
<u>WTH100</u>	(WTH100) Insulated Weathertight Mechanical Hub	Zinc Alloy	1 in.	3.8 in.	5.40 in.
<u>WTH125</u>	(WTH125) Insulated Weathertight Mechanical Hub	Zinc Alloy	1-1/4 in.	3.70 in.	5.30 in.
<u>WTH150</u>	(WTH150) Insulated Weathertight Mechanical Hub	Zinc Alloy	1-1/2 in.	3.8 in.	5.30 in.
<u>WTH200</u>	(WTH200) Insulated Weathertight Mechanical Hub	Zinc Alloy	2 in.	5.2 in.	3.7 in.
<u>WTH250</u>	(WTH250) Insulated Weathertight Mechanical Hub	Zinc Alloy	2-1/2 in.	5.3 in.	3.80 in.
<u>WTH300</u>	(WTH300) Insulated Weathertight Mechanical Hub	Zinc Alloy	3 in.	3.6 in.	5.20 in.

<u>Item #</u>	<u>Item Name</u>	<u>Material</u>	<u>Size</u>	<u>Package Length</u>	<u>Package Width</u>
<u>WTH350</u>	(WTH350) Insulated Weathertight Mechanical Hub	Zinc Alloy	3-1/2 in.	5.91 in.	4.8 in.
<u>WTH400</u>	(WTH400) Insulated Weathertight Mechanical Hub	Zinc Alloy	4 in.	3.6 in.	5.40 in.