

Product Data Sheet

132X122

Replace "X" with 1, 2 or 3 for number of poles

Power Splicer Stud Block
200 Amps, 600 Volts (AC/DC)
1,000V AC/DC CE (IEC 60947-7-1)



Wire Range:

Line side: 1/4 - 20 X 9/16 Stud

Load Side: 1/4 - 20 X 9/16 Stud

Insulator base adders and 1 pole product can be snapped together through integral dovetails to create variable pole power blocks.

7.5 x 35 mm din rail or panel mountable

Electrical Ratings:

- 200 Amps, intended for conductors prepared with Listed crimp-type terminals.
- CE Rated Voltage (U_i): 1,000 V AC/DC per IEC 60947-7-1
- UL/CSA Voltage Rating: 600 Volts AC/DC (UL 1059 Class C, Use Group - General Industrial)
- Factory and Field Wiring

NOTE: Use outside these ratings must be judged in end-use application

Mechanical Ratings:

- Insulator base temperature: -40°C to 125°C (257°F) UL RTI
- Flammability rating of insulator base: UL 94 V-0

Materials:

- Bus bar: Copper, tin plated
- Insulator base: Glass filled polycarbonate (Thermoplastic)
- Connector mounting screw: Steel, zinc plated
- Threaded Studs: Brass, Tin plated
- Nuts: Steel, Zinc plated (packed loose)
- Washers (flat and split): Steel, Zinc plated (packed loose)

Agency Approvals:

- UL Recognized, UL 1059 Terminal Block Standard, File No. XCFR2.E62806
- CSA Certified, CSA C22.2 No. 158, File No. LR19766
- CE compliant to IEC 60947-7-1
- RoHS Compliant

