THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NUMBER	WEIGHT
DPA48688TGY	2.36 lb (1070.48 g)

NOTES:
1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AS WELL AS OPTIONAL ICONS.
2. MATERIAL:
   PANEL HOUSING: STEEL
   RJ45 MODULES: THERMOPLASTIC RESIN UL94V-0
   PUNCHDOWN BLOCKS: THERMOPLASTIC RESIN UL94V-0
   BEZEL ASSEMBLY: THERMOPLASTIC RESIN UL94H-B
   RETENTION CAP: THERMOPLASTIC RESIN UL94V-0
3. 48 PORT ANGLED PATCH PANEL 8 POSITION 8 WIRE.
4. THE PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS.
5. FOUR (4) 12-24 X 1/2" ROUND HEAD SCREWS AND (4) M6x1x15MM METRIC SCREWS ARE PROVIDED FOR FASTENING TO RACKS.
6. DIMENSIONS IN BRACKETS ARE IN METRIC.
7. USE 110 STYLE TERMINATION TOOL FOR PUNCHDOWN.
8. RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS.



MODEL FILENAME: M02088AD_2RU_48PORT_ANG_PANEL_ASSY_03
DRAWING FILENAME: M02479JC_DC239_00A
SIZE: A

DP6 PLUS 48 PORT ANGLED PATCH PANEL CUSTOMER DRAWING

PANDUIT™ CORP.
TINLEY PARK, ILL 60477

I.I. NUMBER
PRODUCT SPEC
WORK INSTRUCTION

THIRD ANGLE PROJECTION

ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED.
DIMENSIONAL TOLERANCES ARE:
(.X) ±.03 (.XXX) ±.005
(.XX) ±.01 ANGLES ± 1°

SCALE .25 : 1

DRAWN BY: LZ
DATE: 3-4-06
CHK'D
REVIEW DRAWING NUMBERS

PART NO. SEE CHART
DRAWING NO. 02479-239

REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH
R	3-4-06	LZ		RELEASED TO PRODUCTION	02479-239			