

StanZoil NL-34/334

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Neoprene
- **Length (inches)** 12
- **Wrist** Straight cuff
- **Colour/Color** Black / Blue
- **Interior finish** Textile support
- **Exterior finish** Non-slip grip
- **Size / EAN** 6 7 8 9
- **Packaging** 12 pairs/box - 72 pairs/carton



PERFORMANCE RESULTS

Certification category



X2XXXX



ACJKL




3121

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374




RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS




SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS



For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL
www.mapa-pro.com

DESCRIPTION AND GENERAL PROPERTIES

- Soft, absorbent interlock knit cotton liner adds comfort, easy on-off, high-and low-temperature protection.
- 1.5 AQL - Quality Assurance

MAIN FIELDS OF USE

Mechanical industry

- Maintenance in wet environments (water, oil, greases, hydrocarbons)

Chemical industry

- Handling and transporting chemicals

Petroleum industry

- Handling

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.

-It is not recommended for persons sensitized to natural latex proteins and dithiocarbamates to use these gloves.

- Put the gloves on dry, clean hands.

Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.

- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.

Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their original packaging at a temperature not below 5°C.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (dilutents, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : using the gloves or submitting them to another cleaning or laundering process that is not specifically recommended can alter their performance levels

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

Food contact US

FDA 21CFR 177.2600

LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council. This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).