

Inductive Rectangular Sensors



Housing Style - Rectangular	Part Number	ID Number	Features	Embeddable	Sensing Range (mm)	Output
18 mm - Nonembeddable, Potted-In Cable 	Ni 5-Q18-AN6X	M4614607			5	3-Wire DC NPN
	Ni 5-Q18-AP6X	M4614606			5	3-Wire DC PNP
	Ni10-Q18-AP6X	M4652210	Extended Range		10	3-Wire DC PNP

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Front Cap/ Face	Power LED	Output LED	Cable Length /Jacket	Wiring Diagram #	Wiring Diagrams
10-30 VDC	500	≤200	-25 to +70	IP 67	PBT	PBT	N/A	YE	2M/PVC	1	<p>Diagram 1</p>
10-30 VDC	500	≤200	-25 to +70	IP 67	PBT	PBT	N/A	YE	2M/PVC	2	<p>Diagram 2</p>
10-30 VDC	500	≤200	-25 to +70	IP 67	PBT	PBT	N/A	YE	2M/PVC	2	

Rectangular

For material descriptions see page M36.