

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
8 mm - Embeddable, Miniature Threaded, eurofast® Quick Disconnect 	Bi 1.5-G08-AN6X-H1341	S4603700		1.5	3-Wire DC NPN
	Bi 1.5-G08-AN7X-H1341	S4701126	<i>TTL Compatible</i>	1.5	
	Bi 2-G08-AN6X-H1341	S4602600	<i>Ext. Range</i>	2	
	Bi 1.5-G08-AP6X-H1341	S4603600		1.5	3-Wire DC PNP
	Bi 2-G08-AP6X-H1341	S4602500	<i>Ext. Range</i>	2	

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #	Wiring Diagrams
10-30 VDC	3000	≤150	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4T-*	1	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> Diagram 1 </div> <div style="border: 1px solid black; padding: 5px;"> Diagram 2 </div>
	3000	≤150	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4T-*	1	
	3000	≤150	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4T-*	1	
10-30 VDC	3000	≤150	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4T-*	2	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> Diagram 1 </div> <div style="border: 1px solid black; padding: 5px;"> Diagram 2 </div>
	3000	≤150	-25 to +70	IP 67	SS	PA 12	N/A	YE	RK 4T-*	2	

*Length in meters.