

# Inductive Washdown Sensors Ferrite Core



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
<b>8 mm - Embeddable, Quick Disconnect</b>  	Bi 1.5-EG08WD-AN6X-H1341	S4602211	<b>Washdown</b>	1.5	3-Wire DC NPN
	Bi 1.5-EG08WD-AP6X-H1341	S4602210	<b>Washdown</b>	1.5	3-Wire DC PNP

For detailed sensor specifications see Section M.  
 Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	End Cap	Output LED	Mating Cordset, Cable Length/Mat.	Wiring Diagram #	Wiring Diagrams
10-30 VDC	3000	≤150	-10 to +85	IP 68,69K	SS	PA 12	N/A	YE	RK 4T-*	1	<p><b>Diagram 1</b></p>
10-30 VDC	3000	≤150	-10 to +85	IP 68,69K	SS	PA 12	N/A	YE	RK 4T-*	2	<p><b>Diagram 2</b></p>

\* Length in meters.

Washdown Ferrite Core

Harsh Duty

For material descriptions see page M36.