

3-Wire eurofast® Cordsets, Standard Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 250 VAC/300 VDC, 4 A



Cordsets

| Housing Style | Part Number | Cable | Features | Pinout |
|---------------|--------------|---|---|--------|
| | WK 4T-* | AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528-*M† | flexlife® | |
| | WK 4T-*/S90 | AWM PUR Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50518-*M† | Cut/Abrasion Immune | |
| | WK 4T-*/S101 | AWM TPE Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50940-*M† | flexLife-10, High Flex Over 10 Million Cycles | |
| | WK 4T-*/S529 | AWM PUR/Heavy Braid Double Jacket Yellow 3x20 AWG 80°C 5.2 mm OD Cable #RF50832-*M† | Cut/Abrasion Immune Braided Mechanical Shield | |
| | WK 4T-*/S824 | PLTC AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50829-*M† | Tray Rated | |
| | WK 4T-*/S715 | AWM PVC Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50674-*M† | flexlife | |
| | WK 4T-*/S760 | AWM PVC Black 3x20 AWG 105°C 5.2 mm OD Cable #RF50795-*M† | flexlife | |
| | WK 4T-*/S618 | AWM PVC Grey 3x20 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50611-*M† | RFI/EMI Shielding | |

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "WK .."; "WKK .." indicates nylon and "WKV .." indicates 316 stainless steel.
 † See Section N for reelfast® cable information.