

6-Wire eurofast® Cordsets, "C" Style Medium Plug Body

- Right Angle Male Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
	WSC 6T-*	AWM PVC Grey 6x24 AWG 105°C 5.7 mm OD Cable #RF50608-*M [†]	flexlife®	
	WSC 6T-*/S90	AWM PUR Grey 6x24 AWG 80°C 5.7 mm OD Cable #RF50646-*M [†]	Cut/Abrasion Immune	
WSC 6T-*/S101	AWM TPE Grey 6x24 AWG 105°C 5.7 mm OD Cable #RF50910-*M [†]	flexlife-10, high flex over 10 million cycles		
WSC 6T-*/S90/S760	AWM PUR Black 6x24 AWG 80°C 5.7 mm OD Cable #RF50728-*M [†]	Cut/Abrasion Immune, Black Cable	1. BN 2. WH 3. BU 4. BK 5. GY 6. PK	
	WSC 6T-*/S529	AWM PVC Yellow 6x24 AWG 105°C 6.2 mm OD Cable #RF51120-*M [†]	Cut/Abrasion immune, braided mechanical shield	
	WSC 6T-*/S849/S1052	AWM PVC Grey 6x24 AWG 105°C 6.2 mm OD Cable #RF51284-*M [†]	flexlife, 22AWG conductors, grey cable	
WSC 6T-*/S618	AWM PVC Grey 6x24 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50610-*M [†]	RF/EMI Shielding		
WSC 6T-*/S653	AWM PVC Grey 5x22 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50609-*M [†]	5 Conductor Foil Shield w/drain wire to Pin 6	1. BN 2. WH 3. BU 4. BK 5. GY 6. Drain	
WSC 6T-*/S90/CS10476	AWM PUR NAMUR Blue 5x24 AWG Foil/Drain 80°C 5.7 mm OD Cable #RF50928-*M [†]	Cut/Abrasion Immune	1. OG 2. RD 3. YE 4. BK 5. BU 6. Drain	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WSC .."; "WSCV .." indicates 316 stainless steel.

† See Section N for reelfast® cable information.