

2, 3 and 4-Wire *minifast*® Cordsets, Heavy Duty

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 600 V, 9 A



| Housing Style | Part Number | Cable | Features | Pinout | |
|---------------|------------------|--|---|-------------------------------|--|
| | WKM 26-*M | STOW PVC Yellow 2x16 AWG 105°C 10.4 mm OD Cable #RF50561-*M† | <i>flexlife</i> ® | 1. WH 2. BK | |
| | WKM 35-*M | STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50537-*M† | <i>flexlife</i> | 1. GN 2. RD/BK 3. RD/WH | |
| | WKM 35-*M/S600 | SOOW CPE Yellow 3x16 AWG 105°C 10.3 mm OD Cable #RF50596-*M† | <i>Weld Flash Immune, Flame Immune</i> | 1. GN 2. RD 3. RD | |
| | WKM 36-*M | STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50536-*M† | <i>flexlife</i> | 1. GN 2. BK 3. WH | |
| | WKM 36D-*M/S1062 | STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50536-*M† | <i>flexlife</i> ® Cable, PVC plug body with PVC contact carriers | | |

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass "WKM .."; "WK .." indicates nylon and "WKV .." indicates 316 stainless steel.
† See Section N for *reelfast*® cable information.