

2, 3 and 4-Wire *minifast*® Cordsets, Heavy Duty

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 600 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	WKM 46-*M	STOW PVC Yellow 4x16 AWG 105°C 11 mm OD Cable #RF50538-*M [†]	<i>flexlife</i>	
	WKM 46-*M/S600	SOOW CPE Yellow 4x16 AWG 105°C 11 mm OD Cable #RF50595-*M [†]	<i>Weld Flash Immune, Flame Immune</i>	1. BK 2. WH 3. RD 4. GN
	WKM 46-*M/S824	TC PVC Yellow 4x16 AWG 90°C 9.6 mm OD Cable #RF51220-*M [†]	<i>Tray Rated</i>	
	WKM 46D-*M/S1062	STOW PVC Yellow 4x16 AWG 105°C 11 mm OD Cable #RF50538-*M [†]	<i>flexlife</i> ® Cable, PVC plug body with PVC contact carriers	
	WKM 47-*M	STOW PVC Yellow 4x16 AWG 105°C 13.2 mm OD Cable #RF50626-*M [†]	<i>flexlife</i>	1. BN 2. WH 3. BU 4. BK

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass "WKM .."; "WK .." indicates nylon and "WKV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.