

5 and 6-Wire *minifast*® Cordsets, Heavy Duty

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 600 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	WKM 55-*M	STOW PVC Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF50540-*M [†]	<i>flexlife</i> ®	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
	WKM 55-*M/S600	SOOW CPE Yellow 5x16 AWG 105°C 13 mm OD Cable #RF50597-*M [†]	<i>Weld Flash Immune, Flame Immune</i>	1. RD 2. RD 3. GN 4. RD 5. RD
	WKM 56-*M	STOW PVC Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF50539-*M [†]	<i>flexlife</i>	
	WKM 56-*M/S1587	STOW TPE Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF51265-*M [†]	<i>weldlife, Weld Flash Immune</i>	
	WKM 56D-*M/S1062	STOW PVC Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF50539-*M [†]	<i>flexlife</i> ® Cable, PVC plug body with PVC contact carriers	
	WKM 66-*M	STOW PVC Yellow 6x16 AWG 105°C 13.2 mm OD Cable #RF50565-*M [†]	<i>flexlife</i>	1. WH 2. RD 3. GN 4. OG 5. BK
	WKM 66D-*M/S1062	STOW PVC Yellow 6x16 AWG 105°C 13.2 mm OD Cable #RF50565-*M [†]	<i>flexlife</i> ® Cable, PVC plug body with PVC contact carriers	1. WH 2. RD 3. GN 4. OG 5. BK 6. BU

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
 Standard coupling nut material is nickel plated brass "WKM .."; "WK .." indicates nylon and "WKV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.