

**19-Pin M16 versafast® Cordsets**

- Right Angle Male Connectors
- For eurofast®/picofast® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 30 VAC/VDC, 3 A



This page was updated 07-8-08

Housing Style	Part Number	Cable	App.	Features	Pinout
	BSWM 19-873-*	AWM PVC Black 19x26 AWG 105°C 7.1 mm OD Cable #RF50873-*M†	19-wire DC applications	flexlife®	A. RD/BU B. WH/GN C. GY D. BN/GN E. GN F. GN/YE G. BK H. WH/YE I. WH/GY K. GY/BN L. GY/PK M. BN N. PK O. YE P. WH R. RD S. VT T. YE/BN U. BU
	BSWM 19-995-*	AWM PVC Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50995-*M†	19-wire DC applications	Cut/Abrasion Immune	
	BSWM 19-996-*/S90	AWM PUR Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50996-*M†			
	BSWM 19-997-*/S101	AWM TPE Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50997-*M†			

Cordsets

\* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.  
 Standard coupling nut material is nickel plated brass.. "BSWM.."; "BSWMK.." indicates nylon and "BSWMV.." indicates 316 stainless steel.  
 † See Section N for reelfast® cable information.