

3-Wire M8 *pico*fast® Cordsets, with LEDs, Threaded Coupling Nut

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 10 VAC/30 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	PKW 3M-P7X2-*	AWM PVC Yellow 3x24 AWG 105°C 4.4 mm OD Cable #RF50642-*M <sup>†</sup>	PNP Signal, <i>flexlife</i> ®	
	PKW 3M-P7X2-*/S90	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50587-*M <sup>†</sup>	PNP Signal, Cut/Abrasion Immune	
	PKW 3M-P7X2-*/S90/S101	AWM PUR Black 3x26 AWG 105°C 4.4 mm OD Cable #RF50723-*M <sup>†</sup>	PNP Signal, Cut/Abrasion Immune, <i>flexlife-10</i> , High Flex - over 10 Million Cycles	
	PKW 3M-N7X2-*/S90/S618	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M <sup>†</sup>	PNP Signal, Cut/Abrasion Immune, EMI/RFI Protection	
	PKW 3M-N7X2-*	AWM PVC Yellow 3x24 AWG 105°C 4.4 mm OD Cable #RF50642-*M <sup>†</sup>	NPN Signal, <i>flexlife</i>	
	PKW 3M-N7X2-*/S90	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50587-*M <sup>†</sup>	NPN Signal, Cut/Abrasion Immune	
	PKW 3M-N7X2-*/S90/S101	AWM PUR Black 3x26 AWG 105°C 4.4 mm OD Cable #RF50723-*M <sup>†</sup>	NPN Signal, Cut/Abrasion Immune, <i>flexlife-10</i> , High Flex - over 10 Million Cycles	
	PKW 3M-N7X2-*/S90/S618	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M <sup>†</sup>	NPN Signal, Cut/Abrasion Immune, EMI/RFI Protection	

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

\*\* Standard coupling material is nickel plated brass.

† See Section N for *reelfast*® cable information.