

3-Wire M12 eurofast® Cordsets, Standard Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



| Housing Style | Part Number | Cable | Features | Pinout |
|---------------|--------------|--|--|--------|
| | RS 4T-* | AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528-*M† | <i>flexlife</i> ® | |
| | RS 4T-*/S90 | AWM PUR Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50518-*M† | <i>Cut/Abrasion Immune</i> | |
| | RS 4T-*/S101 | AWM TPE Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50940-*M† | <i>flexlife-20, High Flex Over 20 Million Cycles</i> | |
| | RS 4T-*/S529 | AWM PUR/Heavy Braid Double Jacket Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50832-*M† | <i>Cut/Abrasion Immune Braided Mechanical Shield</i> | |
| | RS 4T-*/S824 | PLTC AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50829-*M† | <i>Tray Rated</i> | |
| | RS 4T-*/S715 | AWM PVC Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50674-*M† | <i>flexlife</i> | |
| | RS 4T-*/S760 | AWM PVC Black 3x20 AWG 105°C 5.2 mm OD Cable #RF50795-*M† | <i>flexlife</i> | |
| | RS 4T-*/S618 | AWM PVC Grey 3x20 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50611-*M† | <i>RFI/EMI Shielding</i> | |

Cordsets

1. BN
2. N/C
3. BU
4. BK

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RS .."; "RSK .." indicates nylon and "RSV .." indicates 316 stainless steel.
 † See Section N for *reelfast*® cable information.