

8, 10 and 12-Wire M12 *eurofast*® Cordsets, "S" Style, Shielded

- Straight Female Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
<p>RKS ..**</p>	RKS 8T-*	AWM PVC Grey 8x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50813-*M [†]	RFI/EMI	1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD
	RKS 10T-*	AWM PVC Grey 10x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF51006-*M [†]	RFI/EMI	1. WH 6. PK 2. BN 7. BU 3. GN 8. RD 4. YE 9. OG 5. GY 10. TN
	RKS 12T-*	AWM PVC Grey 12x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50988-*M [†]	RFI/EMI	1. WH 7. BU 2. BN 8. RD 3. GN 9. OG 4. YE 10. TN 5. GY 11. BK 6. PK 12. VT

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RKS .."; "RKS SV .." indicates 316 stainless steel..
 † See Section N for *reelfast*® cable information.