

2-6 Wire 7/8" *minifast*® Extreme Duty, Armored Cordsets

- Straight Female Connectors
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 600 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	RKM 28A-*M	MC ITC PLTC PVC Armor Yellow 2x18 AWG 90°C 13.5 mm OD Cable #RF51039-*M [†]	<i>Armor Cable for Extreme Conditions</i>	1. WH 2. BK
	RKM 38A-*M	MC ITC PLTC PVC Armor Yellow 3x18 AWG 90°C 13.5 mm OD Cable #RF51040-*M [†]	<i>Armor Cable for Extreme Conditions</i>	1. GN 2. BK 3. WH
	RKM 48A-*M	MC ITC PLTC PVC Armor Yellow 4x18 AWG 90°C 13.5 mm OD Cable #RF51041-*M [†]	<i>Armor Cable for Extreme Conditions</i>	1. BK 2. WH 3. RD 4. GN
	RKM 58A-*M	MC PVC Armor Yellow 5x18 AWG 90°C 12.2 mm OD Cable #RF51042-*M [†]	<i>Armor Cable for Extreme Conditions</i>	1. WH 2. RD 3. GN 4. OG 5. BK
	RKM 68A-*M	MC PVC Armor Yellow 6x18 AWG 90°C 13 mm OD Cable #RF51043-*M [†]	<i>Armor Cable for Extreme Conditions</i>	1. WH 2. RD 3. GN 4. OG 5. BK 6. BU

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKM .."; "RKV .." indicates 316 stainless steel.

[†] See Section N for *reelfast*® cable information.