





4-Wire *minifast*® Receptacles, Front Mount, 1/2-14 NPSM Threads

- Male Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection



Drawing Number	Part Number	Lead Specs.	Features	Pinout	
 <p>1 RSF ..**</p>	RSF 40-*M	UL, CSA 4x18 AWG 105°C 600 V, 9 A	1/2-14 NPSM Threads, Standard Duty	1. BN 2. WH 3. BU 4. BK	
	RSF 40-*M/S658	UL, CSA 4x18 AWG 105°C 300 V, 9 A			
	RSF 40-*M/S849	UL, CSA 4x22 AWG 105°C 300 V, 5 A			
	RSF 46-*M	UL, CSA 4x16 AWG 105°C 600 V, 9 A	1/2-14 NPSM Threads, Heavy Duty	1. BK 2. WH 3. RD 4. GN	
	RSF 48-*M	UL, CSA 4x18 AWG 105°C 600 V, 9 A	1/2-14 NPSM Threads, Standard Duty		

Receptacles

See page F71 for dimensional drawings.

Standard lead length is 0.3 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated brass. "RSF .."; "RSFV .." indicates 316 stainless steel housing, and "RSFK .." indicates nylon housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.