

3 and 4-Wire Field Wireable Connectors, Standard

- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
B 513(4)1-0	B 5131-0	BS 5131-0	PBT, Black, accepts 3-5 mm cable diameter, solder terminals, accepts up to 24 AWG conductors, 85°C, 60 VAC/ 75 VDC, 4 A, mates with 3-pin threaded cordsets and receptacles	Female Male
BS 513(4)1-0	B 5141-0	BS 5141-0	PBT, Black, accepts 3-5 mm cable diameter, solder terminals, accepts up to 24 AWG conductors, 85°C, 30 VAC/ 36 VDC, 4.0 A, mates with 4-pin threaded cordsets and receptacles	Female Male
B 513(4)3-0	B 5133-0	BS 5133-0	PBT, Black, accepts 3-5 mm cable diameter, screw terminals, accepts up to 22 AWG conductors, 85°C, 60 VAC/ 75 VDC, 4 A, mates with 3-pin threaded cordsets and receptacles	Female Male
BS 513(4)3-0	B 5143-0	BS 5143-0	PBT, Black, accepts 3-5 mm cable diameter, screw terminals, accepts up to 22 AWG conductors, 85°C, 60 VAC/ 75 VDC, 4 A, mates with 4-pin threaded cordsets and receptacles	Female Male