

## 2 and 3-Wire Cordsets, "C" Style Medium Plug Body

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>RKC ..**</b></p>	<p>RKC 4.2T-* WKC 4.2T-*</p>	<p>RSC 4.2T-* WSC 4.2T-*</p>	<p>AWM PVC Yellow, 2x18 AWG, 105°C, 7.2 mm OD, Cable #RF50511-*M†, flexlife®</p>	<p><b>Female</b></p>
<p><b>WKC ..**</b></p>	<p>RKC 4.2T-*/CS10191 WKC 4.2T-*/CS10191</p>	<p>RSC 4.2T-*/CS10191 WSC 4.2T-*/CS10191</p>	<p>AWM PVC NAMUR Blue, 2x18 AWG, 105°C, 7.2 mm OD, Cable #RF50843-*M†, flexlife, Black Plug Body</p>	
<p><b>RSC ..**</b></p>	<p>RKC 4T-* WKC 4T-*</p>	<p>RSC 4T-* WSC 4T-*</p>	<p>ITC/PLTC PVC Yellow, 3x18 AWG, 105°C, 7.2 mm OD, Cable #RF50513-*M†, flexlife, tray rated</p>	
<p><b>WSC ..**</b></p>	<p>RKC 4T-*/S1062 WKC 4T-*/S1062</p>	<p>RSC 4T-*/S1062 WSC 4T-*/S1062</p>	<p>ITC/PLTC PVC Yellow, 3x18 AWG, 105°C, 7.2 mm OD, Cable #RF50513-*M†, flexlife® Cable, PVC plug body with PVC contact carriers, tray rated</p>	<p><b>Male</b></p>

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "RKC .."; "RKC .." indicates stainless steel.

† See Section N for **reelfast**® cable information.