



5-Wire Cordsets, "C" Style Medium Plug Body

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
RKC ..** 	RKC 4.5T-*/S653 WKC 4.5T-*/S653	RSC 4.5T-*/S653 WSC 4.5T-*/S653	ITC/PLTC AWM PVC Grey, 4x22 AWG, 105°C, Foil/Drain, 5.1 mm OD, Cable #RF50773-*M†, RFI/EMI Shielding, Tray Rated	1. BN 2. WH 3. BU 4. BK 5. Drain
WKC ..** 	RKC 4.5T-*/S1538 WKC 4.5T-*/S1538	RSC 4.5T-*/S1538 WSC 4.5T-*/S1538	AWM PVC Grey, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF50630-*M†, flexlife*	1. BN 2. WH 3. BU 4. BK 5. GN/YE
RSC ..** 	RKC 4.5T-*/S715/S849 WKC 4.5T-*/S715/S849	RSC 4.5T-*/S715/S849 WSC 4.5T-*/S715/S849	AWM PVC Yellow, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50684-*M†, flexlife	1. BN 2. WH 3. BU 4. BK 5. GY
WSC ..** 	RKC 4.5T-*/CS10288 WKC 4.5T-*/CS10288	RSC 4.5T-*/CS10288 WSC 4.5T-*/CS10288	AWM PVC Yellow, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF50549-*M†, flexlife*	1. BN 2. WH 3. BU 4. BK 5. GN/YE
	RKC 4.5T-*/S1062 WKC 4.5T-*/S1062	RSC 4.5T-*/S1062 WSC 4.5T-*/S1062	AWM PVC Grey, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50543-*M†, flexlife* Cable, PVC plug body with PVC contact carriers	1. BN 2. WH 3. BU 4. BK 5. GY
	RKC 4.5T-*/S1587 WKC 4.5T-*/S1587	RSC 4.5T-*/S1587 WSC 4.5T-*/S1587	AWM TPE Yellow, 5x18 AWG, 105°C, 6.4 mm OD, Cable #RF51232-*M†, weldlife, Weld Flash Immune	1. BN 2. WH 3. BU 4. BK 5. GY
	RKCN 5T-* WKC 5T-*	RSCN 5T-* WSCN 5T-*	ITC/PLTC PVC NAMUR Blue, 5x22 AWG, 105°C, 6.9 mm OD, Cable #RF50767-*M†, flexlife*, for VBN 40-H1141 MultiBox	1. GN 2. WH 3. OG 4. BK 5. RD



* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKC .."; "RKC V .." indicates stainless steel.

† See Section N for **reelfast**® cable information.