

4 and 5-Wire Cordsets with LEDs

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 10-30 VDC, 4 A



Connector Style	Female Part Number	Features	Pinout	
<p>RKE ..**</p>	WK 4.4T-* -P7X2/S618	AWM PVC Grey, 4x22 AWG, 105°C, 5.1 mm OD, Cable #RF50577-*M†, PNP Signal, EMI/RFI Protection	<p>Female</p>	
	WK 4.4T-* -N7X2/S618	AWM PVC Grey, 4x22 AWG, 105°C, 5.1 mm OD, Cable #RF50577-*M†, NPN Signal, EMI/RFI Protection		
	WK 4.4T-* -P7X2/S824	ITC/PLTC PVC Grey, 4x22 AWG, 105°C, 5.1 mm OD, Cable #RF50698-*M†, PNP Signal, Tray Rated		
	WK 4.4T-* -N7X2/S824	ITC/PLTC PVC Grey, 4x22 AWG, 105°C, 5.1 mm OD, Cable #RF50698-*M†, NPN Signal, Tray Rated		
<p>WK ..**</p>	WK 4.4T-* -P7X2/X0R	PVC Yellow, 4x20 AWG, 80°C, 250°C short term, 5.2 mm OD, Cable #RF50522-*M†, PNP Signal, Weld Flash & High Temp. Immune	<p>1. BN 2. WH 3. BU 4. BK</p>	
	WK 4.4T-* -N7X2/X0R	PVC Yellow, 4x20 AWG, 80°C, 250°C short term, 5.2 mm OD, Cable #RF50522-*M†, NPN Signal, Weld Flash & High Temp Immune		
	WK 4.5T-* -P7X2	AWM PVC Grey, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50543-*M†, PNP Signal, <i>flexlife</i>		<p>1. BN 2. WH 3. BU 4. BK 5. GY</p>
	RKE 4.5T-* -P7X2	AWM PVC Grey, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50543-*M†, PNP Signal, <i>flexlife</i>		

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WK .."; "WKV .." Indicates stainless steel.

† See Section N for **reelfast**® cable information.