



## 4, 5, 6 and 8-Wire Receptacles, with Rotating Coupling Nut

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection



Housing Style	Female Part Number	Features	Pinout
<p>FKM ..*</p> <p>Typical panel cutout is 15.2 mm.</p>	FKM 4.4-*	4x22 AWG, 105°C, 250 V, 4 A, mates with 4-pin cordsets	<ol style="list-style-type: none"> <li>1. BN</li> <li>2. WH</li> <li>3. BU</li> <li>4. BK</li> </ol>
	FKM 4.5-*	5x22 AWG, 105°C, 250 V, 4 A, mates with 5-pin cordsets	<ol style="list-style-type: none"> <li>1. BN</li> <li>2. WH</li> <li>3. BU</li> <li>4. BK</li> <li>5. GY</li> </ol>
	FKM 4.5-*/S653	4x22 AWG, Drain, 105°C, 250 V, 4 A, 5.1 mm OD, mates with 5-pin cordsets, 4 conductors PVC foil Shielded with Drain Wire to pin 5	<ol style="list-style-type: none"> <li>1. BN</li> <li>2. WH</li> <li>3. BU</li> <li>4. BK</li> <li>5. Drain</li> </ol>
	FKM 4.6-*	6x22 AWG, 105°C, 250 V, 2 A Mates with 6-pin Cordsets	<ol style="list-style-type: none"> <li>1. BN</li> <li>2. WH</li> <li>3. BU</li> <li>4. BK</li> <li>5. GY</li> <li>6. PK</li> </ol>
	FKM 6-*	6x24 AWG, 105°C, 60 VAC/75 VDC, 2 A, mates with 6-pin cordsets	<ol style="list-style-type: none"> <li>1. BN</li> <li>2. WH</li> <li>3. BU</li> <li>4. BK</li> <li>5. GY</li> <li>6. PK</li> </ol>
	FKM 8-*	8x24 AWG, 105°C, 60 VAC/75 VDC, 2 A, mates with 8-pin cordsets	<ol style="list-style-type: none"> <li>1. WH</li> <li>2. BN</li> <li>3. GN</li> <li>4. YE</li> <li>5. GY</li> <li>6. PK</li> <li>7. BU</li> <li>8. RD</li> </ol>

Receptacles

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.  
Standard housing material is nickel plated brass.  
To specify PVC jacketed cable, add "/S717" to the end of the part number.