

4, 5 and 6-Wire Receptacles, with Front Lock Nut

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A (4 & 5 pole)
- 60 VAC/75 VDC, 2 A (6 pole)



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>FKD ..*</b></p> <p>Typical panel cutout is 15.2 mm</p>	FKD 4.4-*	FSD 4.4-*	4x22 AWG, 105°C, mates with 4-pin cordsets	<p><b>Female</b></p> <p><b>Male</b></p>
	FKD 4.5-*	FSD 4.5-*	5x22 AWG, 105°C, mates with 5-pin cordsets	<p><b>Female</b></p>
	FKD 4.5-*/S653	FSD 4.5-*/S653	4x22 AWG, Drain, 105°C, 5.1 mm OD, mates with 5-pin cordsets, 4 Conductors PVC foil Shielded with Drain Wire to pin 5	<p><b>Male</b></p>
<p><b>FSD ..*</b></p> <p>Typical panel cutout is 15.2 mm</p>	FKD 6-*	FSD 6-*	6x24 AWG, 105°C, mates with 6-pin cordsets	<p><b>Female</b></p> <p><b>Male</b></p>

\* Length in meters. Standard lead length is 0.5 meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FSD.."; "FSDV.." indicates 316 stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.