

2, 3 and 5-Wire Cordsets, Large Plug Body

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>KBE ..**</p> <p>WKBE ..**</p>	<p>KBE 2T-*</p> <p>WKBE 2T-*</p>	<p>SBE 2T-*</p> <p>WSBE 2T-*</p>	<p>AWM PVC Yellow, 2x18 AWG, 105°C, 7.2 mm OD, Cable #RF50511-*M†, flexlife®</p>	<p>Female</p> <p>Male</p>
<p>KBE 3T-*</p> <p>WKBE 3T-*</p>	<p>KBE 3T-*</p> <p>WKBE 3T-*</p>	<p>SBE 3T-*</p> <p>WSBE 3T-*</p>	<p>AWM PVC Yellow, 3x18 AWG, 105°C, 7.2 mm OD, Cable #RF50520-*M†, flexlife</p>	<p>Female</p>
<p>SBE ..**</p>	<p>KBE 3T-*/S600</p> <p>WKBE 3T-*/S600</p>	<p>SBE 3T-*/S600</p> <p>WSBE 3T-*/S600</p>	<p>SJOOW CPE Yellow, 3x18 AWG, 105°C, 8.0 mm OD, Cable #RF50658-*M†, Weld Flash Immune, Flame Immune</p>	<p>1. GN 2. RD/BK 3. RD/WH</p> <p>Male</p>
<p>SBE ..**</p>	<p>KBE 3T-*/S1587</p> <p>WKBE 3T-*/S1587</p>	<p>SBE 3T-*/S1587</p> <p>WSBE 3T-*/S1587</p>	<p>AWM TPE Yellow, 3x18 AWG, 105°C, 7.2 mm OD, Cable #RF50957-*M†, Weldlife, Weld Flash Immune</p>	
<p>WSBE ..**</p>	<p>KBE 5T-*</p> <p>WKBE 5T-*</p>	<p>SBE 5T-*</p> <p>WSBE 5T-*</p>	<p>AWM PVC Yellow, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF50521-*M†, flexlife</p>	<p>Female</p>
<p>WSBE ..**</p>	<p>KBE 5T-*/S600</p> <p>WKBE 5T-*/S600</p>	<p>SBE 5T-*/S600</p> <p>WSBE 5T-*/S600</p>	<p>SJOOW CPE Yellow, 5x18 AWG, 105°C, 9.3 mm OD, Cable #RF50659-*M†, Weld Flash Immune, Flame Immune</p>	<p>1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK</p>
<p>WSBE ..**</p>	<p>KBE 5T-*/S1587</p> <p>WKBE 5T-*/S1587</p>	<p>SBE 5T-*/S1587</p> <p>WSBE 5T-*/S1587</p>	<p>AWM TPE Yellow, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF50958-*M†, Weldlife, Weld Flash Immune</p>	<p>Male</p>

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** KBE large plug body has no stainless steel or nylon options.

† See Section N for reelfast® cable information.