



## 2, 3 and 4-Wire Receptacles, Front Mount, 1/2-14 NPSM Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



| Housing Style   | Female Part Number | Male Part Number  | Features           | Pinout   |
|---|--------------------|-------------------|--------------------|--|
| <p><b>FKB ...</b></p> <p>Typical panel cutout is 22.5 mm.</p> | FKB 2-*/14.5       | FSB 2-*/14.5      | 2x18 AWG,<br>105°C | <p><b>Female</b></p> <p><b>Male</b></p> <p>1. BN<br/>2. BU</p>                           |
| <p><b>FKB ...</b></p> <p>Typical panel cutout is 22.5 mm.</p> | FKB 3-*/14.5       | FSB 3-*/14.5      | 3x22 AWG,<br>105°C | <p><b>Female</b></p> <p><b>Male</b></p> <p>1. GN<br/>2. RD/BK<br/>3. RD/WH</p>           |
| <p><b>FSB ...</b></p> <p>Typical panel cutout is 22.5 mm.</p> | FKB 3-*/14.5/S690  | FSB 3-*/14.5/S690 | 3x18 AWG,<br>105°C | <p><b>Female</b></p> <p><b>Male</b></p>  |
| <p><b>FSB ...</b></p> <p>Typical panel cutout is 22.5 mm.</p> | FKB 4-*/14.5       | FSB 4-*/14.5      | 4x22 AWG,<br>105°C | <p><b>Female</b></p> <p><b>Male</b></p> <p>1. RD/BK<br/>2. RD/WH<br/>3. RD<br/>4. GN</p> |

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.  
Standard housing material is nickel plated brass."FSB ..".  
To specify PVC jacketed cable, add "/S717" to the end of the part number.