

4, 5 and 6-Wire Receptacles, Front Mount, 1/4-18 NPT Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FKB ...</p> <p>Typical panel cutout is 14.3 mm.</p>		FSB 4-*/18.25/S621	4x18 AWG, 105°C, UL Listed, CSA Recognized	<p>Female</p> <p>Male</p>
	FKB 4-*/18.25	FSB 4-*/18.25	4x22 AWG, 105°C, UL Listed, CSA Recognized	<p>1. RD/BK</p> <p>2. RD/WH</p> <p>3. RD</p> <p>4. GN</p>
		FSB 4-*/18.25/S727	4x22 AWG, 105°C, UL Listed, CSA Recognized	<p>1. BN</p> <p>2. BU</p> <p>3. BK</p> <p>4. WH</p>
<p>FSB ...</p> <p>Typical panel cutout is 14.3 mm.</p>	FKB 5-*/18.25	FSB 5-*/18.25	5x22 AWG, 105°C, UL Listed, CSA Recognized	<p>Female</p> <p>Male</p>
	FKB 5-*/18.25/S690	FSB 5-*/18.25/S690	5x18 AWG, 105°C, UL Listed, CSA Recognized	<p>1. RD/WH</p> <p>2. RD</p> <p>3. GN</p> <p>4. RD/YE</p> <p>5. RD/BK</p>
	FKB 6-*/18.25	FSB 6-*/18.25	6x22 AWG, 105°C	<p>Female</p> <p>Male</p>

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.
 Standard housing material is nickel plated brass."FSB ..". "FSBV.." indicates stainless steel housing.
 To specify PVC jacketed cable, add "/S717" to the end of the part number.