

TURCK 7/8" minifast® Connectivity Products



2 and 3-Wire Cordsets, Heavy Duty

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 600 V, 10 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>RKM ..**</p>	RKM 26-*M WKM 26-*M	RSM 26-*M WSM 26-*M	STOW PVC Yellow 2x16 AWG, 105°C, 10.4 mm OD, Cable #RF50561-*M†, flexlife*	<p>Female</p> <p>Male</p>
<p>WKM ..**</p>	RKM 35-*M WKM 35-*M	RSM 35-*M WSM 35-*M	STOW PVC Yellow, 3x16 AWG, 105°C, 10.4 mm OD, Cable #RF50537-*M†, flexlife	<p>Female</p>
<p>RSM ..**</p>	RKM 35-*M/S600 WKM 35-*M/S600	RSM 35-*M/S600 WSM 35-*M/S600	SOOW CPE Yellow, 3x16 AWG, 105°C, 10.3 mm OD, Cable #RF50596-*M†, Weld Flash Immune, Flame Immune	<p>Female</p>
<p>WSM ..**</p>	RKM 36-*M WKM 36-*M	RSM 36-*M WSM 36-*M	STOW PVC Yellow, 3x16 AWG, 105°C, 10.4 mm OD, Cable #RF50536-*M†, flexlife	<p>Male</p>
	RKM 36-*M/S1587 WKM 36-*M/S1587	RSM 36-*M/S1587 WSM 36-*M/S1587	SEOW/STOW TPE Yellow, 3x16 AWG, 105°C, 10.4 mm OD, Cable #RF51563-*M†, weldlife, Weld Flash Immune	

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKM .." indicates stainless steel, and "RKVH .." indicates stainless steel hex.
 † See Section N for **reelfast**® cable information.