


TURCK 1" minifast® Connectivity Products



8-Wire Cordsets, B-Size Heavy Duty

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 600 VAC/DC, 8 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>RKM ..**</p>	RKM 86-*M WKM 86-*M	RSM 86-*M WSM 86-*M	ITC PLTC PVC Yellow, 8x16 AWG, 105°C, 11.2 mm OD, Cable #RF51032-*M†, <i>flexlife</i> *	<p>Female</p> <p>1. OG 2. BU 3. WH/BK 4. BK 5. WH 6. RD 7. GN 8. RD/BK</p> <p>Male</p>
<p>WKM ..**</p>	RKM 86-*M/S90 WKM 86-*M/S90	RSM 86-*M/S90 WSM 86-*M/S90	ITC/PLTC TPU Yellow, 8x16 AWG, 105°C, 11.2 mm OD, Cable #RF51139-*M†, Cut/abrasion Immune	
<p>RSM ..**</p>	RKM 86-*M/S101 WKM 86-*M/S101	RSM 86-*M/S101 WSM 86-*M/S101	AWM TPE Yellow, 8x16, 105°C, 9.6 mm OD, Cable #RF51050-*M†, <i>flexlife</i> -20, High flex - over 20 million cycles	
<p>WSM ..**</p>	RKM 86-*M/S1587 WKM 86-*M/S1587	RSM 86-*M/S1587 WSM 86-*M/S1587	AWM TPE Yellow, 8x16 AWG, 105°C, 10.5 mm OD, Cable #RF51011-*M†, <i>weldlife</i> , Weld flash Immune	

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKM .."; "RKV .." indicates stainless steel.

† See Section N for **reelfast**® cable information.