



5-Wire Receptacles, Front Mount, 1/2-14 NPSM Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>RKF ..</p> <p>Typical panel cutout 22.5 mm</p>	RKF 50-*M	RSF 50-*M	5x18 AWG, 105°C, 600 V, 9 A, standard duty	1. BK 2. BU 3. GN/YE 4. BN 5. WH
	RKF 50-*M/S849	RSF 50-*M/S849	5x22 AWG, 105°C, 300 V, 5 A, standard duty	<p>Female</p>
<p>RSF ..</p> <p>Typical panel cutout is 22.5 mm</p>	RKF 511-*M	RSF 511-*M	5x18 AWG, 105°C, 600 V, 9 A, automotive color code	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
	RKF 511-*M/S849	RSF 511-*M/S849	5x22 AWG, 105°C, 300 V, 5 A, automotive color code	<p>Male</p>
	RKF 55-*M	RSF 55-*M	5x16 AWG, 105°C, 600 V, 10 A, automotive color code	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
	RKF 56-*M	RSF 56-*M	5x16 AWG, 105°C, 600 V, 10 A, heavy duty	1. WH 2. RD 3. GN 4. OG 5. BK
		RSF 56-*M/S849	5x22 AWG, 105°C, 300 V, 5 A, heavy duty	
	RKF 58-*M	RSF 58-*M	5x18 AWG, 105°C, 300 V, 9 A, heavy duty	

Receptacles

Standard lead length is 0.3 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated brass. "RSF .."; "RSFV .." indicates stainless steel housing, and "RSFK .." indicates nylon housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.